

ExpTime Tableaux for the Description Logic SHIQ Based on Global State Caching and Integer Linear Feasibility Checking

Linh Anh Nguyen

Institute of Informatics, University of Warsaw
Banacha 2, 02-097 Warsaw, Poland
nguyen@mimuw.edu.pl

Abstract. We give the first EXPTIME (complexity-optimal) tableau decision procedure for checking satisfiability of a knowledge base in the description logic *SHIQ*. The complexity is measured using binary representation for numbers. Our procedure is based on global state caching and integer linear feasibility checking.

Keywords: automated reasoning, description logics, global state caching, integer linear feasibility

1 Introduction

Automated reasoning in description logics (DLs) has been an active research area for more than two decades. It is useful, for example, for the Semantic Web in engineering and querying ontologies [1]. One of basic reasoning problems in DLs is to check satisfiability of a knowledge base in a considered DL. Most of other reasoning problems in DLs are reducible to this one [2]. In this paper we study the problem of checking satisfiability of a knowledge base in the DL *SHIQ*, which extends the basic DL *ACC* with transitive roles, hierarchies of roles, inverse roles and quantified number restrictions.

Tobies in his PhD thesis [35] proved that the problem is EXPTIME-complete (even when numbers are coded in binary). On page 127 of [35] he wrote: “*The previous EXPTIME-completeness results for SHIQ rely on the highly inefficient automata construction of Definition 4.34 used to prove Theorem 4.38 and, in the case of knowledge base reasoning, also on the wasteful pre-completion technique used to prove Theorem 4.42. Thus, we cannot expect to obtain an implementation from these algorithms that exhibits acceptable runtimes even on relatively “easy” instances. This, of course, is a prerequisite for using SHIQ in real-world applications.*”

Together with Horrocks and Sattler, Tobies therefore developed a tableau decision procedure for *SHIQ* [18,35]. Later, in [17] Horrocks and Sattler gave a tableau decision procedure for *SHOIQ*, and in [16] Horrocks et al. gave a tableau decision procedure for *SROIQ*. Both the logics *SHOIQ* and *SROIQ* are more expressive than *SHIQ*, but they also have higher complexity (*SHOIQ* is NEXPTIME-complete and *SROIQ* is N2EXPTIME-complete). According to the recent survey [20], the third generation ontology reasoners that support *SHIQ* or *SROIQ* are FaCT, FaCT++, RACER, Pellet, KAON2 and HermiT. The reasoners FaCT, FaCT++, RACER and Pellet are based on tableaux like the ones in [18,17,16], KAON2 is based on a translation into disjunctive Datalog [21], and HermiT is based on hypertableaux [5]. Traditional tableau decision procedures like the ones in [18,17,16] can be implemented with various optimization techniques to increase efficiency. However, such procedures use backtracking to deal with disjunction ($\sqcup$) and “or”-branching (e.g., the “choice” operation [18]) and despite advanced blocking techniques (e.g., pairwise anywhere blocking [18]), their complexities are non-optimal. In particular, the decision procedure for *SHIQ* given in [18,35] has complexity NEXPTIME when unary representation is used for numbers, and has complexity N2EXPTIME when binary representation is used.

By applying global caching [33,10], together with colleagues (Goré, Szalas and Dunin-Kępcicz) we have developed complexity-optimal (EXPTIME) tableau decision procedures for several modal and description logics with EXPTIME complexity [7,8,9,27,28,29,30,31,3].

In [8,28,31,3] analytic cuts are used to deal with inverse roles and converse modal operators. As cuts may be not efficient in practice, Goré and Widmann developed the first cut-free EXPTIME tableau decision procedures, based on global state caching, for the DL $\mathcal{ALCI}$ (for the case without ABoxes) [12] and CPDL [13]. We have applied global state caching for the modal logic CPDL_{reg} [24] and the DLs $\mathcal{ALCI}$ [25] and $\mathcal{SHI}$ [26] for the case with ABoxes to obtain cut-free EXPTIME tableau decision procedures for them.

As $\mathcal{SHIQ}$ is a well-known and useful DL, developing a complexity-optimal tableau decision procedure for checking satisfiability of a knowledge base in $\mathcal{SHIQ}$ is very desirable. The lack of such a procedure in a relatively long period up to the current work suggests that the problem is not easy at all. For example, in [12] Goré and Widmann wrote “*The extension to role hierarchies and transitive roles should not present difficulties, but the extension to include nominals and qualified number restrictions is not obvious to us.*”.

In this paper we give the first EXPTIME tableau decision procedure for checking satisfiability of a knowledge base in the DL $\mathcal{SHIQ}$. The complexity is measured using binary representation for numbers. Our procedure is based on global state caching and integer linear feasibility checking. Both of them are essential for our procedure in order to have the optimal complexity. Global state caching can be replaced by global caching plus cuts, which still guarantee the optimal complexity. However, we choose global state caching to avoid inefficient cuts although it makes our procedure more complicated.

We are aware of only Farsiniamarj’s master thesis [4] (written under supervision of Haarslev) as a work that directly combines tableaux with integer programming. Some related works [32,14,15] are discussed in that thesis and we refer the reader there for details. In [4] Farsiniamarj presented a hybrid tableau calculus for the DL $\mathcal{SHQ}$ (a restricted version of $\mathcal{SHIQ}$ without inverse roles), which is based on the so-called atomic decomposition technique and combines arithmetic and logical reasoning. He stated that “*The most prominent feature of this hybrid calculus is that it reduces reasoning about qualified number restrictions to integer linear programming. [...] In comparison to other standard description logic reasoners, our approach demonstrates an overall runtime improvement of several orders of magnitude.*” [4]. On the complexity matter, Farsiniamarj wrote “*the complexity of the algorithm seems to be characterized by a double-exponential function*” [4, page 79]. That is, his algorithm for $\mathcal{SHQ}$ is not complexity-optimal.

Combining global (state) caching and integer linear feasibility checking to obtain a complexity-optimal (EXPTIME) tableau decision procedure for $\mathcal{SHIQ}$ is not a simple exercise as one might think. Integer linear programming using the branch and bound method [19] is known since 1960, Pratt’s idea on global caching for PDL [33] is known since 1980 (the term “global caching” is absent in [33]), a formal formulation of global caching for some modal and description logics [8,10] is known since 2007 (if not earlier [7]), but the first complexity-optimal (EXPTIME) tableau decision procedure for $\mathcal{SHIQ}$ is only proposed now, in the current paper. As for experts on tableaux with global caching, it took us a few months to make the idea of the combination precise and one year since our paper on $\mathcal{SHI}$ [26] to the current paper (on $\mathcal{SHIQ}$).¹ Our method of exploiting integer linear programming is different from Farsiniamarj’s one [4]: in order to avoid nondeterminism, we only check feasibility but do not find and use solutions of the considered set of constraints as in [4].

The rest of this paper is structured as follows. In Section 2 we recall the notation and semantics of $\mathcal{SHIQ}$ and introduce an integer feasibility problem for DLs. In Section 3 we present our tableau decision procedure for $\mathcal{SHIQ}$. We start by introducing data structures and the tableau framework. We then present illustrative examples. After that we specify our tableau rules in detail. At the end of the section we present theoretical results about our tableau decision procedure. Those results are proved in Section 4. We conclude this work in Section 5.

¹ Of course, we were busy with teaching duties and other papers.

2 Preliminaries

2.1 Notation and Semantics of SHIQ

Our language uses a finite set $\mathbf{C}$ of *concept names*, a finite set $\mathbf{R}$ of *role names*, and a finite set $\mathbf{I}$ of *individual names*. We use letters like A and B for concept names, r and s for role names, and a and b for individual names. We refer to A and B also as *atomic concepts*, and to a and b as *individuals*.

For $r \in \mathbf{R}$, let r^- be a new symbol, called the *inverse* of r . Let $\mathbf{R}^- = \{r^- \mid r \in \mathbf{R}\}$ be the set of *inverse roles*. For $r \in \mathbf{R}$, define $(r^-)^- = r$. A *role* is any member of $\mathbf{R} \cup \mathbf{R}^-$. We use letters like R and S to denote roles.

An (*SHIQ*) *RBox* $\mathcal{R}$ is a finite set of role axioms of the form $R \sqsubseteq S$ or $R \circ R \sqsubseteq R$. By $\text{ext}(\mathcal{R})$ we denote the least extension of $\mathcal{R}$ such that:

- $R \sqsubseteq R \in \text{ext}(\mathcal{R})$ for any role R
- if $R \sqsubseteq S \in \text{ext}(\mathcal{R})$ then $R^- \sqsubseteq S^- \in \text{ext}(\mathcal{R})$
- if $R \circ R \sqsubseteq R \in \text{ext}(\mathcal{R})$ then $R^- \circ R^- \sqsubseteq R^- \in \text{ext}(\mathcal{R})$
- if $R \sqsubseteq S \in \text{ext}(\mathcal{R})$ and $S \sqsubseteq T \in \text{ext}(\mathcal{R})$ then $R \sqsubseteq T \in \text{ext}(\mathcal{R})$.

By $R \sqsubseteq_{\mathcal{R}} S$ we mean $R \sqsubseteq S \in \text{ext}(\mathcal{R})$, and by $\text{trans}_{\mathcal{R}}(R)$ we mean $(R \circ R \sqsubseteq R) \in \text{ext}(\mathcal{R})$. If $R \sqsubseteq_{\mathcal{R}} S$ then R is a *subrole* of S (w.r.t. $\mathcal{R}$). If $\text{trans}_{\mathcal{R}}(R)$ then R is a *transitive role* (w.r.t. $\mathcal{R}$). A role is *simple* (w.r.t. $\mathcal{R}$) if it is neither transitive nor has any transitive subroles (w.r.t. $\mathcal{R}$).

Concepts in SHIQ are formed using the following BNF grammar, where n is a nonnegative integer and S is a simple role:

$$C, D ::= \top \mid \perp \mid A \mid \neg C \mid C \sqcap D \mid C \sqcup D \mid \exists R.C \mid \forall R.C \mid \geq n S.C \mid \leq n S.C$$

We use letters like C and D to denote arbitrary concepts.

A *TBox* is a finite set of axioms of the form $C \sqsubseteq D$ or $C \doteq D$.

An *ABox* is a finite set of *assertions* of the form $a:C$, $R(a, b)$ or $a \neq b$.

A *knowledge base* in SHIQ is a tuple $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$, where $\mathcal{R}$ is an RBox, $\mathcal{T}$ is a TBox and $\mathcal{A}$ is an ABox.

We say that a role S is *numeric* w.r.t. a knowledge base $KB = \langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ if:

- it is simple w.r.t. $\mathcal{R}$ and occurs in a concept $\geq n S.C$ or $\leq n S.C$ in KB , or
- $S \sqsubseteq_{\mathcal{R}} R$ and R is numeric w.r.t. KB , or
- S^- is numeric w.r.t. KB .

We will simply call such an S a *numeric role* when KB is clear from the context.

A *formula* is defined to be either a concept or an ABox assertion. We use letters like φ , ψ and ξ to denote formulas. Let $\text{null}:C$ stand for C . We use α to denote either an individual or null. Thus, $\alpha:C$ is a formula of the form $a:C$ or $\text{null}:C$ (which means C).

An *interpretation* $\mathcal{I} = \langle \Delta^{\mathcal{I}}, \cdot^{\mathcal{I}} \rangle$ consists of a non-empty set $\Delta^{\mathcal{I}}$, called the *domain* of $\mathcal{I}$, and a function $\cdot^{\mathcal{I}}$, called the *interpretation function* of $\mathcal{I}$, that maps each concept name A to a subset $A^{\mathcal{I}}$ of $\Delta^{\mathcal{I}}$, each role name r to a binary relation $r^{\mathcal{I}}$ on $\Delta^{\mathcal{I}}$, and each individual name a to an element $a^{\mathcal{I}} \in \Delta^{\mathcal{I}}$. The interpretation function is extended to inverse roles and complex concepts as follows, where $\#Z$ denotes the cardinality of a set Z :

$$\begin{aligned} (r^-)^{\mathcal{I}} &= \{ \langle x, y \rangle \mid \langle y, x \rangle \in r^{\mathcal{I}} \} & \top^{\mathcal{I}} &= \Delta^{\mathcal{I}} & \perp^{\mathcal{I}} &= \emptyset \\ (\neg C)^{\mathcal{I}} &= \Delta^{\mathcal{I}} - C^{\mathcal{I}} & (C \sqcap D)^{\mathcal{I}} &= C^{\mathcal{I}} \cap D^{\mathcal{I}} & (C \sqcup D)^{\mathcal{I}} &= C^{\mathcal{I}} \cup D^{\mathcal{I}} \\ (\exists R.C)^{\mathcal{I}} &= \{ x \in \Delta^{\mathcal{I}} \mid \exists y [\langle x, y \rangle \in R^{\mathcal{I}} \text{ and } y \in C^{\mathcal{I}}] \} \\ (\forall R.C)^{\mathcal{I}} &= \{ x \in \Delta^{\mathcal{I}} \mid \forall y [\langle x, y \rangle \in R^{\mathcal{I}} \text{ implies } y \in C^{\mathcal{I}}] \} \\ (\geq n R.C)^{\mathcal{I}} &= \{ x \in \Delta^{\mathcal{I}} \mid \# \{ y \mid \langle x, y \rangle \in R^{\mathcal{I}} \text{ and } y \in C^{\mathcal{I}} \} \geq n \} \\ (\leq n R.C)^{\mathcal{I}} &= \{ x \in \Delta^{\mathcal{I}} \mid \# \{ y \mid \langle x, y \rangle \in R^{\mathcal{I}} \text{ and } y \in C^{\mathcal{I}} \} \leq n \}. \end{aligned}$$

Note that $(r^-)^{\mathcal{I}} = (r^{\mathcal{I}})^{-1}$ and this is compatible with $(r^-)^- = r$.

For a set Γ of concepts, define $\Gamma^{\mathcal{I}} = \{x \in \Delta^{\mathcal{I}} \mid x \in C^{\mathcal{I}} \text{ for all } C \in \Gamma\}$.

The relational composition of binary relations R_1, R_2 is denoted by $R_1 \circ R_2$.

An interpretation $\mathcal{I}$ is a *model of an RBox* $\mathcal{R}$ if for every axiom $R \sqsubseteq S$ (resp. $R \circ R \sqsubseteq R$) of $\mathcal{R}$, we have that $R^{\mathcal{I}} \subseteq S^{\mathcal{I}}$ (resp. $R^{\mathcal{I}} \circ R^{\mathcal{I}} \subseteq R^{\mathcal{I}}$). Note that if $\mathcal{I}$ is a model of $\mathcal{R}$ then it is also a model of $\text{ext}(\mathcal{R})$.

An interpretation $\mathcal{I}$ is a *model of a TBox* $\mathcal{T}$ if for every axiom $C \sqsubseteq D$ (resp. $C \doteq D$) of $\mathcal{T}$, we have that $C^{\mathcal{I}} \subseteq D^{\mathcal{I}}$ (resp. $C^{\mathcal{I}} = D^{\mathcal{I}}$).

An interpretation $\mathcal{I}$ is a *model of an ABox* $\mathcal{A}$ if for every assertion $a : C$ (resp. $R(a, b)$ or $a \neq b$) of $\mathcal{A}$, we have that $a^{\mathcal{I}} \in C^{\mathcal{I}}$ (resp. $\langle a^{\mathcal{I}}, b^{\mathcal{I}} \rangle \in R^{\mathcal{I}}$ or $a^{\mathcal{I}} \neq b^{\mathcal{I}}$).

An interpretation $\mathcal{I}$ is a *model of a knowledge base* $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ if $\mathcal{I}$ is a model of all $\mathcal{R}$, $\mathcal{T}$ and $\mathcal{A}$. A knowledge base $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ is *satisfiable* if it has a model.

An interpretation $\mathcal{I}$ *satisfies* a concept C (resp. a set X of concepts) if $C^{\mathcal{I}} \neq \emptyset$ (resp. $X^{\mathcal{I}} \neq \emptyset$). A set X of concepts is *satisfiable w.r.t. an RBox* $\mathcal{R}$ *and a TBox* $\mathcal{T}$ if there exists a model of $\mathcal{R}$ and $\mathcal{T}$ that satisfies X . For $X = \mathcal{A} \cup \mathcal{A}'$, where $\mathcal{A}$ is an ABox and $\mathcal{A}'$ is a set of assertions of the form $\neg R(a, b)$ or $a \doteq b$, we say that X is *satisfiable w.r.t. an RBox* $\mathcal{R}$ *and a TBox* $\mathcal{T}$ if there exists a model $\mathcal{I}$ of $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ such that: $\langle a^{\mathcal{I}}, b^{\mathcal{I}} \rangle \notin R^{\mathcal{I}}$ for all $(\neg R(a, b)) \in \mathcal{A}'$, and $a^{\mathcal{I}} = b^{\mathcal{I}}$ for all $(a \doteq b) \in \mathcal{A}'$. In that case, we also say that $\mathcal{I}$ is a model of $\langle \mathcal{R}, \mathcal{T}, X \rangle$.

2.2 An Integer Feasibility Problem for Description Logics

For dealing with number restrictions in $\mathcal{SHIQ}$, we consider the following integer feasibility problem:

$$\begin{aligned} \sum_{j=1}^m a_{i,j} \cdot x_j \bowtie_i b_i, \quad \text{for } 1 \leq i \leq l; \\ x_j \geq 0, \quad \text{for } 1 \leq j \leq m; \end{aligned}$$

where each $a_{i,j}$ is either 0 or 1, each x_j is a variable standing for a natural number, each $\bowtie_i$ is either $\leq$ or $\geq$, each b_i is a natural number encoded by using no more than n bits (i.e., $b_i \leq 2^n$). We call this an IFDL(l, m, n)-problem (a problem of Integer Feasibility for Description Logics with size specified by l, m, n). The problem is *feasible* if it has a solution, and is *infeasible* otherwise. By solving an IFDL(l, m, n)-problem we mean checking its feasibility.

Lemma 2.1. *If l and m are (at most) exponential in n then every IFDL(l, m, n)-problem can be solved in (at most) exponential time in n .* $\square$

Proof. Assume that l and m are (at most) exponential in n and consider any IFDL(l, m, n)-problem. Let $J = \{1 \leq j \leq m \mid \text{there exists } 1 \leq i \leq l \text{ with } a_{i,j} = 1 \text{ and } \bowtie_i = '\leq'\}$. For each $j \in J$, let $c_j = \min\{b_i \mid 1 \leq i \leq l \text{ and } a_{i,j} = 1\}$ and we have that $x_j \leq c_j$. For any $j \in \{1, \dots, m\} - J$, if $a_{i,j} = 1$ then $\bowtie_i$ is $\geq$ and x_j can be as big as we want. Thus, without affecting feasibility of the problem we can delete constraint number i if it uses some $a_{i,j} = 1$ with $j \notin J$. So, we assume that $J = \{1, \dots, m\}$, which means we have a constraint $x_j \leq c_j$ for every variable x_j , where $c_j \leq 2^n$. Now we can check feasibility of the problem by using the branch and bound method [19]. One round for branching and bounding runs in polynomial time in $l + m$. Each round reduces the sum of lengths of intervals for variables by 1. As variables are bounded by 2^n and l and m are (at most) exponential in n , the checking can be done in (at most) exponential time in n . $\square$

3 ExpTime Tableaux for SHIQ

3.1 Data Structures and the Tableau Framework

We assume that concepts and ABox assertions are represented in negation normal form (NNF), where $\neg$ occurs only directly before atomic concepts.² We use $\overline{C}$ to denote the NNF of $\neg C$, and for $\varphi = (a:C)$, we use $\overline{\varphi}$ to denote $a:\overline{C}$. For simplicity, we treat axioms of $\mathcal{T}$ as concepts representing global assumptions: an axiom $C \sqsubseteq D$ is treated as $\overline{C} \sqcup D$, while an axiom $C \doteq D$ is treated as $(\overline{C} \sqcup D) \sqcap (\overline{D} \sqcup C)$. That is, we assume that $\mathcal{T}$ consists of concepts in NNF. Thus, an interpretation $\mathcal{I}$ is a model of $\mathcal{T}$ iff $\mathcal{I}$ validates every concept $C \in \mathcal{T}$. As this way of handling the TBox is not efficient in practice, the absorption technique like the one discussed in [30] can be used to improve the performance of our algorithm.

We define tableaux as rooted graphs. Such a graph is a tuple $G = \langle V, E, \nu \rangle$, where V is a set of nodes, $E \subseteq V \times V$ is a set of edges, $\nu \in V$ is the root, and each node $v \in V$ has a number of attributes. If there is an edge $\langle v, w \rangle \in E$ then we call v a *predecessor* of w , and call w a *successor* of v . Attributes of tableau nodes are:

- $Type(v) \in \{\text{state}, \text{non-state}\}$. If $Type(v) = \text{state}$ then we call v a *state*, else we call v a *non-state* (or an *internal* node). If $Type(v) = \text{state}$ and $\langle v, w \rangle \in E$ then $Type(w) = \text{non-state}$. If $\langle v, w \rangle \in E$ and $Type(w) = \text{state}$ then v has only w as a successor.
 - $SType(v) \in \{\text{complex}, \text{simple}\}$ is called the subtype of v . If $SType(v) = \text{complex}$ then we call v a *complex node*, else we call v a *simple node*. The graph never contains edges from a simple node to a complex node. If $\langle v, w \rangle$ is an edge from a complex node v to a simple node w then $Type(v) = \text{state}$ and $Type(w) = \text{non-state}$. If $Type(v) = \text{state}$ and $\langle v, w \rangle \in E$ then $SType(w) = \text{simple}$. The root of the graph is a complex node.
 - $Status(v) \in \{\text{unexpanded}, \text{p-expanded}, \text{f-expanded}, \text{incomplete}, \text{closed}, \text{open}\}$, where p-expanded and f-expanded mean “partially expanded” and “fully expanded”, respectively. $Status(v)$ may be p-expanded or incomplete only when $Type(v) = \text{state}$. The status of a node may only be changed:
 - from unexpanded to any other status; or
 - from p-expanded to f-expanded, incomplete or closed; or
 - from f-expanded to incomplete, closed or open.
- The values incomplete, closed and open are thus “final”. Roughly speaking, closed means “unsatisfiable” and open means “satisfiable” in a certain sense.
- $Label(v)$ is a finite set of formulas, called the label of v . The label of a complex node consists of ABox assertions, while the label of a simple node consists of concepts.
 - $RFmls(v)$ is a finite set of formulas, called the set of reduced formulas of v .
 - $StatePred(v) \in V \cup \{\text{null}\}$ is called the state-predecessor of v . It is available only when $Type(v) = \text{non-state}$. If v is a non-state and G has no paths connecting a state to v then $StatePred(v) = \text{null}$. Otherwise, G has exactly one state u that is connected to v via a path not containing any other states, and we have that $StatePred(v) = u$.
 - $ATPred(v) \in V$ is called the after-transition-predecessor of v . It is available only when $Type(v) = \text{non-state}$ and $SType(v) = \text{simple}$. In that case, if $v_0 = StatePred(v)$ ($\neq \text{null}$) then there is exactly one successor v_1 of v_0 such that every path connecting v_0 to v must go through v_1 , and we have that $ATPred(v) = v_1$. We define **AfterTrans**(v) = ($ATPred(v) = v$). If **AfterTrans**(v) holds then v has exactly one predecessor u and u is a state.
 - $CELabel(v)$ is a tuple $\langle CELabelT(v), CELabelR(v), CELabelI(v) \rangle$ called the coming edge label of v . It is available only when **AfterTrans**(v) holds. In that case:
 - $CELabelT(v) \in \{\text{testingClosedness}, \text{checkingFeasibility}\}$ (the letter T stands for “type”),
 - $CELabelR(v) \subseteq \mathbf{R} \cup \mathbf{R}^-$ (is a set of roles),

² Every formula can be transformed to an equivalent formula in NNF. This normal form is good, e.g., for the implemented tableau decision procedure reported in [23].

- $CELabelI(v) \in \mathbf{I} \cup \{\text{null}\}$ (for $u = StatePred(v)$ being the only predecessor of v , if $SType(u) = \text{complex}$ then $CELabelI(v)$ is an individual, else $CELabelI(v) = \text{null}$).
- $FmlsRC(v)$ is a set of formulas, called the set of formulas required by converse (inverse) for v . It is available only when $Type(v) = \text{state}$.
- $FmlFB(v)$ is a formula, called the formula for branching on at v . It is available only when $Type(v) = \text{state}$ and $Status(v) = \text{incomplete}$.
- $ILConstraints(v)$ is a set of integer linear constraints. It is available only when $Type(v) = \text{state}$. The constraints use variables x_w indexed by successors w of v with $CELabelT(w) = \text{checkingFeasibility}$. Such a variable x_w specifies how many copies of w will be used as successors of v .

We will use also new concept constructors $\preceq n R.C$ and $\succeq n R.C$, where R is a numeric role. The difference between $\preceq n R.C$ and $\leq n R.C$ is that, for checking $\preceq n R.C$, we do not have to look to predecessors of the node. The aim for $\succeq n R.C$ is similar. We use $\preceq n R.C$ and $\succeq n R.C$ only as syntactic representations of some expressions, and do not provide semantics for them. We define

$$\text{FullLabel}(v) = \text{Label}(v) \cup RFmls(v) - \{\text{formulas of the form } \alpha: (\preceq n R.C) \text{ or } \alpha: (\succeq n R.C)\}.$$

By the *local graph* of a state v we mean the subgraph of G consisting of all the paths starting from v and not containing any other states. Similarly, by the local graph of a non-state v we mean the subgraph of G consisting of all the paths starting from v and not containing any states.

Remark 3.1. We give here a further description/intuition about the structure of G :

- If u is a state of G and $v_1, \dots, v_k$ are all successors of u then:
 - the local graph of each v_i is a directed acyclic graph,
 - if $i, j \in \{1, \dots, k\}$ and $i \neq j$ then the local graphs of v_i and v_j are disjoint,
 - the local graph of u is a graph rooted at u and consisting of the edges from u to $v_1, \dots, v_k$ and the local graphs of $v_1, \dots, v_k$,
 - if w is a node in the local graph of some v_i then $StatePred(w) = u$ and $ATPred(w) = v_i$.
- If u is a state of G then:
 - each edge from outside the local graph of u to the local graph of u must end at u ,
 - each edge outgoing from the local graph of u must start from a non-state and is the only outgoing edge of that non-state.
- G consists of:
 - the local graph of the root ν ,
 - the local graphs of states,
 - edges coming to states.
- Each complex node of G is like an ABox (more formally: its label is an ABox), which can be treated as a graph whose vertices are named individuals. On the other hand, a simple node of G stands for an unnamed individual. If there is an edge from a simple non-state v to (a simple node) w then v and w stand for the same unnamed individual. An edge from a complex node v to a simple node w with $CELabelI(w) = a$ can be treated as an edge from the named individual a (an inner node of the graph representing v) to the unnamed individual corresponding to w , and that edge is via the roles from $CELabelR(w)$.
- G consists of two layers: the layer of complex nodes and the layer of simple nodes. The former layer consists of the local graph of the root ν together with a number of complex states and edges coming to them. The edges from the layer of complex nodes to the layer of simple nodes are exactly the edges outgoing from those complex states. There are no edges from the layer of simple nodes to the layer of complex nodes. $\square$

We apply global state caching: if v_1 and v_2 are different states then $Label(v_1) \neq Label(v_2)$. If v is a non-state such that **AfterTrans**(v) holds then we also apply global caching for the local graph of v : if w_1 and w_2 are different nodes of the local graph of v then $Label(w_1) \neq Label(w_2)$. Creation of a new node or a new edge is done by Procedures **ConToSucc** (connect to a successor) or **NewSucc** (new successor) given on page 7. These procedures create a connection from a node v given as the first parameter to a node with attributes *Type*, *SType*, *Label*, *RFmls*, *CELabel* specified by the remaining parameters. The difference between these procedures is that **NewSucc** always creates a new node and a new connection, while **ConToSucc** first checks whether there exists a node that can be used as a proxy for the successor to be created. **NewSucc** is called outside **ConToSucc** only when v (the first parameter) is a state.

Function NewSucc($v, type, sType, label, rFmls, ceLabel$)

Global data: a rooted graph $\langle V, E, \nu \rangle$.

Purpose: create a new successor for v .

- 1 create a new node w , $V := V \cup \{w\}$, if $v \neq \text{null}$ then $E := E \cup \{\langle v, w \rangle\}$;
 - 2 $Type(w) := type$, $SType(w) := sType$, $Status(w) := \text{unexpanded}$;
 - 3 $Label(w) := label$, $RFmls(w) := rFmls$;
 - 4 if $type = \text{non-state}$ then
 - 5 | if $v = \text{null}$ or $Type(v) = \text{state}$ then $StatePred(w) := v$, $ATPred(w) := w$
 - 6 | else $StatePred(w) := StatePred(v)$, $ATPred(w) := ATPred(v)$;
 - 7 | if $Type(v) = \text{state}$ then $CELabel(w) := ceLabel$;
 - 8 else $FmlsRC(w) := \emptyset$, $ILConstraints(w) := \emptyset$;
 - 9 return w
-

Function FindProxy($type, sType, v_1, label$)

Global data: a rooted graph $\langle V, E, \nu \rangle$.

- 1 if $type = \text{state}$ then $W := V$ else $W :=$ the nodes of the local graph of v_1 ;
 - 2 if there exists $w \in W$ such that $Type(w) = type$ and $SType(w) = sType$ and $Label(w) = label$ then return w else return null
-

Function ConToSucc($v, type, sType, label, rFmls, ceLabel$)

Global data: a rooted graph $\langle V, E, \nu \rangle$.

Purpose: connect a non-state v to a successor, which is created if necessary.

- 1 if $type = \text{state}$ then $v_1 := \text{null}$ else $v_1 := ATPred(v)$;
 - 2 $w := \text{FindProxy}(type, sType, v_1, label)$;
 - 3 if $w \neq \text{null}$ then $E := E \cup \{\langle v, w \rangle\}$, $RFmls(w) := RFmls(w) \cup rFmls$
 - 4 else $w := \text{NewSucc}(v, type, sType, label, rFmls, ceLabel)$;
 - 5 return w
-

From now on, let $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ be a knowledge base in NNF of the logic $\mathcal{SHIQ}$, with $\mathcal{A} \neq \emptyset$.³ In this section we present a tableau calculus $C_{\mathcal{SHIQ}}$ for checking satisfiability of $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$. A $C_{\mathcal{SHIQ}}$ -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ is a rooted graph $G = \langle V, E, \nu \rangle$ constructed as follows:

Initialization: At the beginning, $V = \{\nu\}$, $E = \emptyset$, and ν is the root with $Type(\nu) = \text{non-state}$, $SType(\nu) = \text{complex}$, $Status(\nu) = \text{unexpanded}$, $Label(\nu) = \mathcal{A} \cup \{(a : C) \mid C \in \mathcal{T} \text{ and } a \text{ is an individual occurring in } \mathcal{A}\}$, $StatePred(\nu) = \text{null}$, $RFmls(\nu) = \emptyset$.

Rules' Priorities and Expansion Strategies: The graph is then expanded by the following rules, which will be specified shortly:

³ If $\mathcal{A}$ is empty, we can add $a : \top$ to it, where a is a special individual.

- (UPS) rules for updating statuses of nodes,
- (US) a unary static expansion rule,
- (KCC) rules for keeping converse compatibility,
- (NUS) a non-unary static expansion rule,
- (FS) forming-state rules,
- (TP) a transitional partial-expansion rule,
- (TF) a transitional full-expansion rule.

Each of the rules is parametrized by a node v . We say that a rule is *applicable* to v if it can be applied to v to make changes to the graph. The rules (UPS), (US), (KCC) (in the first three items of the above list) have highest priorities, and are ordered decreasingly by priority. If none of them is applicable to any node, then choose a node v with status **unexpanded** or **p-expanded**, choose the first rule applicable to v among the rules in the last four items of the above list, and apply it to v . Any strategy can be used for choosing v , but it is worth to choose v for expansion only when v could affect the status of the root ν of the graph, i.e., only when there may exist a path from ν to v without any node of status **incomplete**, **closed** or **open**.

Note that the priorities of the rules are specified by the order in the above list, but the rules (UPS), (US), (KCC) are checked globally (technically, they are triggered immediately when possible), while the remaining rules are checked for a chosen node.

The construction of the graph ends when the root ν receives status **closed** or **open** or when every node that may affect the status of ν (i.e., reachable from ν via a path without nodes with status **incomplete**, **closed** or **open**) has been fully expanded (i.e., has status **f-expanded**).

Remark 3.2. To give a deeper intuition behind the structure of a C_{SHIQ} -tableau G constructed for a knowledge base $KB = \langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$, assume that the knowledge base is satisfiable and let us briefly describe how a model $\mathcal{I}$ for KB can be constructed from G . A precise description will be given in the proof of completeness of the calculus. As we will see, the root ν must have status different from **closed** and there exists a complex state v_k with status different from **closed**. $Label(v_k)$ is an ABox that forms the base for the constructed model $\mathcal{I}$. Each named individual a occurring in that ABox is used as an element of the domain of $\mathcal{I}$; role assertions in that ABox specify edges between those elements in $\mathcal{I}$; concept assertions in that ABox specify whether a named individual a is an instance of a given atomic concept in $\mathcal{I}$. The rest of $\mathcal{I}$ consists of disjoint trees rooted at those named elements, which may be infinite. Each element of the domain of $\mathcal{I}$ corresponds either to one of those named individuals or to a simple state of G with status different from **closed**. It is possible that only a number of simple states of G are used for constructing $\mathcal{I}$, and each simple state of G may correspond to many elements of the domain of $\mathcal{I}$ (due to global state caching).

Let y be an element of the domain of $\mathcal{I}$. How successors of y in $\mathcal{I}$ can be constructed?

If y corresponds to a named individual a then let W be the set of successors w of v_k such that: either $CELabelT(w) = \text{testingClosedness}$ and we set $n_w = 1$; or $CELabelT(w) = \text{checkingFeasibility}$, $CELabelI(w) = a$ and the value of x_w in a fixed solution for $ILConstraints(v_k)$, denoted by n_w , is greater than 0.

If y corresponds to a simple state u of G then let W be the set of successors w of u such that: either $CELabelT(w) = \text{testingClosedness}$ and we set $n_w = 1$; or $CELabelT(w) = \text{checkingFeasibility}$ and the value of x_w in a fixed solution for $ILConstraints(u)$, denoted by n_w , is greater than 0.

For each $w \in W$, there must exist a path in G starting from (the non-state) w , going through some or zero other non-states and ending at a state w' with status different from **closed**. For each $w \in W$, we create n_w successors for y (in $\mathcal{I}$) that correspond to w' , using edges labeled by the roles from $CELabelR(w)$. Roughly speaking, all nodes in the path from w to w' are stitched together to make a successor for y , which is then cloned n_w times. The set of atomic concepts such a successor must be an instance of in $\mathcal{I}$ consists of the atomic concepts in $Label(w')$.

Notice that non-states are like “or”-nodes, while states are more sophisticated than “and”-nodes. The transitional partial-expansion rule deals with non-numeric roles, while the transitional full-expansion rule deals with numeric roles. $\square$

3.2 Illustrative Examples

Before specifying the tableau rules in detail, we present simple examples to illustrate some ideas (but not all aspects) of our method. Despite that these examples refer to the tableau rules, we choose this place for presenting them because the examples are quite intuitive and the reader can catch the ideas of our method without knowing the detailed rules. He or she can always consult the rules in the next subsection.




Fig. 1. An illustration for Example 3.3: part I. The graph (a) is the graph constructed until checking converse compatibility for v_1 . In each node, we display the formulas of the node's label. The root ν is expanded by the forming-state rule (FS₂). The complex state v_1 is expanded by the transitional partial-expansion rule, with $CELabelT(v_2) = \text{testingClosedness}$, $CELabelR(v_2) = \{r, s, s^-\}$ (s and s^- are included because $r \sqsubseteq_{\mathcal{R}} s$ and $r \sqsubseteq_{\mathcal{R}} s^-$) and $CELabelI(v_2) = a$. The simple non-states v_2 and v_3 are expanded by the unary static expansion rule (the concepts $\forall r.\neg A$ and $\forall r^-\neg A$ are added into $Label(v_4)$ because $\forall s.\neg A \in Label(v_3)$, $r \sqsubseteq_{\mathcal{R}} s$ and $r^- \sqsubseteq_{\mathcal{R}} s$). The node v_1 is the only state. We have, for example, $StatePred(v_4) = v_1$ and $ATPred(v_4) = v_2$. Checking converse compatibility for v_1 using v_4 (i.e., using the facts that $\{\forall s.\neg A, \forall r^-\neg A\} \subset Label(v_4)$, $StatePred(v_4) = v_1$, $ATPred(v_4) = v_2$, $CELabelT(v_2) = \text{testingClosedness}$, $CELabelR(v_2) = \{r, s, s^-\}$, $CELabelI(v_2) = a$, $r^- \sqsubseteq_{\mathcal{R}} s$ and $trans_{\mathcal{R}}(R)$ holds), $Status(v_1)$ is set to **incomplete** and $FmlsRC(v_1)$ is set to $\{a : \neg A, a : \forall s.\neg A\}$. This results in the graph (b). The construction is then continued by re-expanding the node ν . See Figure 2 for the continuation.




Fig. 2. An illustration for Example 3.3: part II. This is a $CSHIQ$ -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$. As in the part I, in each node we display the formulas of the node's label. The root ν is re-expanded by deleting the edge $\langle \nu, v_1 \rangle$ and connecting ν to a new complex non-state v_5 . The node v_5 is expanded using the unary static expansion rule (the assertions $a : \forall r. \neg A$ and $a : \forall r^-. \neg A$ are added into $Label(v_6)$ because $a : \forall s. \neg A \in Label(v_5)$, $r \sqsubseteq_{\mathcal{R}} s$ and $r^- \sqsubseteq_{\mathcal{R}} s$). The complex non-state v_6 is expanded using the forming-state rule (FS₂). The complex state v_7 is expanded using the transitional partial-expansion rule, with $CELabelT(v_8) = \text{testingClosedness}$, $CELabelR(v_8) = \{r, s, s^-\}$ (s and s^- are included because $r \sqsubseteq_{\mathcal{R}} s$ and $r \sqsubseteq_{\mathcal{R}} s^-$) and $CELabelI(v_8) = a$. The simple non-state v_8 is expanded using the unary static expansion rule. Since $\{A, \neg A\} \subset Label(v_9)$, the simple non-state v_9 receives status **closed**. After that the nodes $v_8, \dots, v_5$ and ν receive status **closed** in subsequent steps. The nodes v_1 and v_7 are the only states.




Fig. 3. An illustration of the tableau described in Example 3.4. The marked nodes v_4, v_8, v_9, v_{10} are states.

Example 3.3. This example is based on an example in the long version of our paper [26] on *SHI*. Let

$$\begin{aligned}\mathcal{R} &= \{r \sqsubseteq s, \quad r^- \sqsubseteq s, \quad s \circ s \sqsubseteq s\} \\ \mathcal{T} &= \{\exists r.(A \sqcap \forall s.\neg A)\} \\ \mathcal{A} &= \{a: \top\}.\end{aligned}$$

In Figures 1 and 2 we illustrate the construction of a C_{SHIQ} -tableau for the knowledge base $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$. At the end the root ν receives status closed. By Theorem 3.7 given later in this paper, $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ is unsatisfiable. As a consequence, $\langle \mathcal{R}, \mathcal{T}, \emptyset \rangle$ is also unsatisfiable. $\square$

Example 3.4. Let us construct a C_{SHIQ} -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$, where $\mathcal{R} = \emptyset$, $\mathcal{T} = \emptyset$ and

$$\mathcal{A} = \{a: \forall r.A_1, \quad a: \leq 3r.A_1, \quad a: \exists r.A_2, \quad a: \geq 2r.A_3, \quad r(a,b), \quad b: (\neg A_1 \sqcup \neg A_2), \quad b: \neg A_3\}$$

An illustration of the tableau is given in Figure 3.

At the beginning, the graph has only the root ν which is a complex non-state with $Label(\nu) = \mathcal{A}$.

Since $\{a: \forall r.A_1, r(a,b)\} \subset Label(\nu)$, applying the unary static expansion rule to ν , we connect it to a new complex non-state v_1 with $Label(v_1) = Label(\nu) \cup \{b: A_1\}$.

Since $b: (\neg A_1 \sqcup \neg A_2) \in Label(v_1)$, applying the non-unary static expansion rule to v_1 , we connect it to two new complex non-states v_2 and v_3 with

$$\begin{aligned}Label(v_2) &= Label(v_1) - \{b: (\neg A_1 \sqcup \neg A_2)\} \cup \{b: \neg A_1\} \\ Label(v_3) &= Label(v_1) - \{b: (\neg A_1 \sqcup \neg A_2)\} \cup \{b: \neg A_2\}.\end{aligned}$$

Since both $b:A_1$ and $b:\neg A_1$ belong to $Label(v_2)$, the node v_2 receives status **closed**.

Applying the forming-state rule (FS₂) to v_3 , we connect it to a new complex state v_4 with

$$Label(v_4) = Label(v_3) \cup \{a:\preceq 2r.A_1, a:\succeq 1r.A_2, a:\succeq 2r.A_3\}.$$

The assertion $a:\preceq 2r.A_1 \in Label(v_4)$ is due to $a:\leq 3r.A_1 \in Label(v_3)$ and the fact that $\{r(a, b), b:A_1\} \subset Label(v_3)$. The assertion $a:\succeq 1r.A_2 \in Label(v_4)$ is due to $a:\exists r.A_2 \in Label(v_3)$ and the fact that $b:\neg A_2 \in Label(v_3)$. Similarly, the assertion $a:\succeq 2r.A_3 \in Label(v_4)$ is due to $a:\geq 2r.A_3 \in Label(v_3)$ and the fact that $b:\neg A_3 \in Label(v_3)$. When realizing the requirements for a at v_4 , we will not have to pay attention to the relationship between a and b .

Applying the transitional partial-expansion rule to v_4 , we change its status to **p-expanded**. After that, applying the transitional full-expansion rule to v_4 , we connect it to new simple non-states v_5 , v_6 and v_7 with $CELabelT$ equal to **checkingFeasibility**, $CELabelR$ equal to $\{r\}$, $CELabelI$ equal to a , $Label(v_5) = \{A_1, A_2\}$, $Label(v_6) = \{A_1, A_3\}$ and $Label(v_7) = \{A_1, A_2, A_3\}$. The creation of v_5 is caused by $a:\succeq 1r.A_2 \in Label(v_4)$, while the creation of v_6 is caused by $a:\succeq 2r.A_3 \in Label(v_4)$. The node v_7 results from merging v_5 and v_6 . Furthermore, $ILConstraints(v_4)$ consists of $x_{v_i} \geq 0$, for $5 \leq i \leq 7$, and

$$\begin{aligned} x_{v_5} + x_{v_6} + x_{v_7} &\leq 2 \\ x_{v_5} + x_{v_7} &\geq 1 \\ x_{v_6} + x_{v_7} &\geq 2. \end{aligned}$$

The set $ILConstraints(v_4)$ is feasible, e.g., with $x_{v_5} = 0$ and $x_{v_6} = x_{v_7} = 1$.

Applying the forming-state rule (FS₁) to v_5 (resp. v_6 , v_7), we connect it to a new simple state v_8 (resp. v_9 , v_{10}) with the same label.

Expanding the nodes v_8 , v_9 and v_{10} , their statuses change to **p-expanded** and then to **f-expanded**. The graph cannot be modified anymore and becomes a C_{SHIQ} -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$, with $Status(\nu) \neq \text{closed}$. By Theorem 3.7 (given later in this paper), the considered knowledge base $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ is satisfiable. Using the solution $x_{v_5} = 0$, $x_{v_6} = x_{v_7} = 1$ for $ILConstraints(v_4)$, we can extract from the graph a model $\mathcal{I}$ for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ with $\Delta^{\mathcal{I}} = \{a, b, v_9, v_{10}\}$, $a^{\mathcal{I}} = a$, $b^{\mathcal{I}} = b$, $A_1^{\mathcal{I}} = \{b, v_9, v_{10}\}$, $A_2^{\mathcal{I}} = \{v_{10}\}$, $A_3^{\mathcal{I}} = \{v_9, v_{10}\}$ and $r^{\mathcal{I}} = \{\langle a, b \rangle, \langle a, v_9 \rangle, \langle a, v_{10} \rangle\}$. $\square$

Example 3.5. Let us construct a C_{SHIQ} -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$, where $\mathcal{R} = \emptyset$, $\mathcal{T} = \emptyset$ and

$$\mathcal{A} = \{a:\exists r.A, a:\forall r.(\neg A \sqcup \neg B), a:\geq 1000r.B, a:\leq 1000r.(A \sqcup B)\}.$$

An illustration of the tableau is given in Figure 4.

At the beginning, the graph has only the root ν which is a complex non-state with $Label(\nu) = \mathcal{A}$. Applying the forming-state rule (FS₂) to ν , we connect it to a new complex state v_1 with

$$Label(v_1) = Label(\nu) \cup \{a:\succeq 1r.A, a:\geq 1000r.B, a:\preceq 1000r.(A \sqcup B)\}.$$

Applying the transitional partial-expansion rule to v_1 , we change its status to **p-expanded**. After that, applying the transitional full-expansion rule to v_1 , connect it to new simple non-states $v_2, \dots, v_7$ with $CELabelT$ equal to **checkingFeasibility**, $CELabelR$ equal to $\{r\}$, $CELabelI$ equal to a , and

$$\begin{aligned} Label(v_2) &= \{A, \neg A \sqcup \neg B, A \sqcup B\} \\ Label(v_3) &= \{A, \neg A \sqcup \neg B, \neg A \sqcap \neg B\} \\ Label(v_4) &= \{B, \neg A \sqcup \neg B, A \sqcup B\} \\ Label(v_5) &= \{B, \neg A \sqcup \neg B, \neg A \sqcap \neg B\} \\ Label(v_6) &= \{A, B, \neg A \sqcup \neg B, A \sqcup B\} \\ Label(v_7) &= \{A, B, \neg A \sqcup \neg B, \neg A \sqcap \neg B\}. \end{aligned}$$




Fig. 4. An illustration of the tableau described in Example 3.5.

Note that $\neg A \sqcap \neg B$ is the NNF of $A \sqcup B$. The nodes v_2 and v_3 are created due to $a : \succeq 1 r.A \in \text{Label}(v_1)$. The nodes v_4 and v_5 are created due to $a : \succeq 1000 r.B \in \text{Label}(v_1)$. The node v_6 results from merging v_2 and v_4 . The node v_7 results from merging v_3 and v_5 . Furthermore, $\text{ILConstraints}(v_1)$ consists of $x_{v_i} \geq 0$, for $2 \leq i \leq 7$, and

$$\begin{aligned}
 x_{v_2} + x_{v_3} + x_{v_6} + x_{v_7} &\geq 1 \\
 x_{v_4} + x_{v_5} + x_{v_6} + x_{v_7} &\geq 1000 \\
 x_{v_2} + x_{v_4} + x_{v_6} &\leq 1000.
 \end{aligned}$$

Applying the unary static expansion rule to v_3 , we connect it to a new simple non-state v_8 with $\text{Label}(v_8) = \{A, \neg A, \dots\}$. The status of v_8 is then updated to **closed** and propagated back to make the status of v_3 also become **closed**, which causes addition of the constraint $x_{v_3} = 0$ into the set $\text{ILConstraints}(v_1)$.

Similarly, applying the unary static expansion rule to v_5 , we connect it to a new simple non-state v_9 with $\text{Label}(v_9) = \{B, \neg B, \dots\}$. The status of v_9 is then updated to **closed** and propagated back to make the status of v_5 also become **closed**, which causes addition of the constraint $x_{v_5} = 0$ into the set $\text{ILConstraints}(v_1)$.

Applying the non-unary static expansion rule to v_6 , we connect it to new simple non-states v_{10} and v_{11} with $\text{Label}(v_{10}) = \{A, \neg A, \dots\}$ and $\text{Label}(v_{11}) = \{B, \neg B, \dots\}$. The statuses of v_{10} and v_{11} are then updated to **closed** and propagated back to make the status of v_6 also become **closed**, which causes addition of the constraint $x_{v_6} = 0$ into the set $\text{ILConstraints}(v_1)$.

Applying the unary static expansion rule to v_7 , we connect it to a new simple non-state v_{12} with $\text{Label}(v_{12}) = \{A, B, \neg A, \neg B, \dots\}$. The status of v_{12} is then updated to **closed** and propagated back to make the status of v_7 also become **closed**, which causes addition of the constraint $x_{v_7} = 0$ into the set $\text{ILConstraints}(v_1)$.

With $x_{v_3} = x_{v_5} = x_{v_6} = x_{v_7} = 0$, $\text{ILConstraints}(v_1)$ becomes infeasible, and $\text{Status}(v_1)$ becomes **closed**. Consequently, ν receives status **closed**. By Theorem 3.7 (given later in this paper), the considered knowledge base $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ is unsatisfiable. $\square$

3.3 The Tableau Rules

In this section we formally specify the tableau rules of our calculus C_{SHIQ} . We also give explanations for them. They are informal and should be understood in the context of the described rule.

The Rules for Updating Status of Nodes:

(UPS₁) The first rule is as follows:

1. if there exists $\alpha : \perp \in \text{Label}(v)$ or $\{\varphi, \bar{\varphi}\} \subseteq \text{FullLabel}(v)$ then $\text{Status}(v) := \text{closed}$
2. else if there exists $a \neq a \in \text{Label}(v)$ then $\text{Status}(v) := \text{closed}$
3. else if $\text{Type}(v) = \text{non-state}$, $\text{SType}(v) = \text{complex}$, $a : (\leq nR.C) \in \text{Label}(v)$ and there are $b_0, \dots, b_n \in \mathbf{I}$ such that, for all $0 \leq i, j \leq n$ with $i \neq j$, we have that $\{R(a, b_i), b_i : C\} \subseteq \text{FullLabel}(v)$ and $\{b_i \neq b_j, b_j \neq b_i\} \cap \text{Label}(v) \neq \emptyset$ then $\text{Status}(v) := \text{closed}$
4. else if $\text{Type}(v) = \text{state}$, $\text{Status}(v) = \text{f-expanded}$ and $\text{ILConstraints}(v)$ is infeasible then $\text{Status}(v) := \text{closed}$
5. else if $\text{Type}(v) = \text{state}$, $\text{Status}(v) = \text{f-expanded}$ and v has no successors then $\text{Status}(v) := \text{open}$.

This rule is applied to v only when v was created or modified in the previous step.

Explanation 1 As stated earlier, informally, **closed** means “unsatisfiable” and **open** means “satisfiable” in a certain sense. The above rule is thus intuitive. For a formal characterization of statuses, we refer the reader to Lemma 4.3 (given on page 22). $\square$

(UPS₂) The second rule states that, if v is a predecessor of a node w then, whenever the status of w changes to **closed** or **open**, the status of v should be updated (as soon as possible by using a priority queue of tasks). The update is done as follows:

1. if $\text{Type}(v) = \text{non-state}$ then
 - (a) if some successor of v received status **open** then $\text{Status}(v) := \text{open}$
 - (b) else if all successors of v have status **closed** then
 - i. $\text{Status}(v) := \text{closed}$
 - ii. if $\text{AfterTrans}(v)$ holds, $\text{CELabelT}(v) = \text{checkingFeasibility}$, $\text{StatePred}(v) = u$ then add the constraint $x_v = 0$ into the set $\text{ILConstraints}(u)$
2. else
 - (a) if some successor w of v with $\text{CELabelT}(w) = \text{testingClosedness}$ received status **closed** then $\text{Status}(v) := \text{closed}$
 - (b) else if some successor w of v with $\text{CELabelT}(w) = \text{checkingFeasibility}$ received status **closed** and $\text{ILConstraints}(v)$ is infeasible then $\text{Status}(v) := \text{closed}$
 - (c) else if
 - $\text{Status}(v) = \text{f-expanded}$,
 - all successors w of v with $\text{CELabelT}(w) = \text{testingClosedness}$ have status **open**, and
 - $\text{ILConstraints}(v) \cup \{x_w = 0 \mid \langle v, w \rangle \in E, \text{CELabelT}(w) = \text{checkingFeasibility} \text{ and } \text{Status}(w) \neq \text{open}\}$ is feasible
 then $\text{Status}(v) := \text{open}$.

Explanation 2

- A non-state is like an “or”-node, whose status is the disjunction of the statuses of its successors, treating **open** as **true** and **closed** as **false**. This explains the items 1a and 1(b)i.
- A state v is more sophisticated than an “and”-node. Its status is different from **closed** iff the following conditions hold:
 - all of its successors with CELabelT equal to **testingClosedness** have status different from **closed**,
 - $\text{ILConstraints}(v) \cup \{x_w = 0 \mid \langle v, w \rangle \in E, \text{CELabelT}(w) = \text{checkingFeasibility} \text{ and } \text{Status}(w) = \text{closed}\}$ is feasible.

The first condition explains the item 2a. The second condition explains the item 2b because, whenever a successor w of v with CELabelT equal to **checkingFeasibility** receives status **closed**, the constraint $x_w = 0$ is added into $\text{ILConstraints}(v)$ (see the item 1(b)ii). The item 2c is justifiable since the premises of the rule expressed by that item are stronger than the conditions listed above. $\square$

The Unary Static Expansion Rule:

- (US) If $Type(v) = \text{non-state}$ and $Status(v) = \text{unexpanded}$ then
1. let $X = \{(\alpha:C) \in Label(v) \mid C \text{ is of the form } D \sqcap D' \text{ or } \geq 0 R.D \text{ or } \leq 0 R.D\}$
 2. let $label = Label(v) \cup \{(\alpha:D), (\alpha:D') \mid \alpha:(D \sqcap D') \in Label(v)\}$
 $\cup \{\alpha:\forall R.\bar{D} \mid (\alpha:\leq 0 R.D) \in Label(v)\}$
 $\cup \{\alpha:\forall R.D \mid \alpha:\forall S.D \in Label(v) \text{ and } R \sqsubseteq_{\mathcal{R}} S\}$
 $\cup \{R^-(b, a) \mid R(a, b) \in Label(v)\}$
 $\cup \{S(a, b) \mid R(a, b) \in Label(v) \text{ and } R \sqsubseteq_{\mathcal{R}} S\}$
 $\cup \{b:D \mid \{a:\forall R.D, R(a, b)\} \subseteq Label(v)\}$
 $\cup \{b:\forall R.D \mid \{a:\forall R.D, R(a, b)\} \subseteq Label(v) \text{ and } trans_{\mathcal{R}}(R)\}$
 $- (X \cup RFmls(v))$
 3. if $label - Label(v) \neq \emptyset$ then
 - (a) $ConToSucc(v, \text{non-state}, SType(v), label, RFmls(v) \cup X, \text{null})$
 - (b) $Status(v) := \text{f-expanded}$.

Explanation 3 This rule makes a necessary expansion for a non-state v by connecting it to only one successor w which is a copy of v with intuitive changes like:

- if $\alpha:(D \sqcap D') \in Label(v)$ then $\alpha:(D \sqcap D')$ in $Label(w)$ is replaced by $\alpha:D$ and $\alpha:D'$ and we remember this by adding it into $RFmls(w)$;
- if $\{a:\forall R.D, R(a, b)\} \subseteq Label(v)$ then we add $b:D$ into $Label(w)$; and so on.

Note that $Label(w) - (Label(v) \cup RFmls(v)) \neq \emptyset$. That is, w contains some “new” formulas. This is to guarantee that the local graph of any non-state is acyclic. $\square$

The Rules for Keeping Converse Compatibility: Rules of this kind are listed below in the decreasing order w.r.t. priority:

- (KCC₁) If $\langle u, v \rangle \in E$ and $Status(v) = \text{incomplete}$ then
1. (we must have that $Type(v) = \text{state}$ and $Type(u) = \text{non-state}$)
 2. delete the edge $\langle u, v \rangle$ from E and re-expand u as follows
 3. if $FmlsRC(v) \neq \emptyset$ then
 - (a) $newLabel := Label(u) \cup FmlsRC(v)$
 - (b) $ConToSucc(u, \text{non-state}, SType(u), newLabel, RFmls(u), \text{null})$
 4. else
 - (a) $newLabel_1 := Label(u) \cup \{FmlFB(v)\}$
 - (b) $ConToSucc(u, \text{non-state}, SType(u), newLabel_1, RFmls(u), \text{null})$
 - (c) $newLabel_2 := Label(u) \cup \{\overline{FmlFB(v)}\}$
 - (d) $ConToSucc(u, \text{non-state}, SType(u), newLabel_2, RFmls(u), \text{null})$.

Explanation 4 We have that v is a state with status *incomplete* and it is the only successor of u . The first expansion of u (by connecting to v) was not a good move and we re-expand u (only once) as follows. We first delete the edge $\langle u, v \rangle$. Next, if $FmlsRC(v) \neq \emptyset$ (i.e., there are formulas that should be added into v), then we connect u to a node with label equal to $Label(u) \cup FmlsRC(v)$ (this node is a replacement for v). If $FmlsRC(v) = \emptyset$ then the reason of $Status(v) = \text{incomplete}$ is that we wanted to have either $FmlFB(v)$ or its negation in $Label(v)$. So, in that case we connect u to two successors, one with label $Label(u) \cup \{FmlFB(v)\}$ and the other with label $Label(u) \cup \{\overline{FmlFB(v)}\}$. The node v is useful for later: whenever we expand a node u' using the forming-state rule by connecting it to v we know immediately that we should re-expand it. The other nodes in the local graph of v can be deleted to save memory. However, we keep them for our presentation to make the proofs easier. $\square$

- (KCC₂) If $Type(v) = \text{state}$, $Status(v) = \text{p-expanded}$ and only the rules for updating status and the unary static rule were applied to the nodes in the local graph of v that are different from v then

1. $X := \emptyset$
2. for each node w in the local graph of v do
 - (a) let $w_0 = ATPred(w)$ and $\alpha = CELabelI(w_0)$
 - (b) $X := X \cup \{\alpha : C \mid \text{there exist } R \in CELabelR(w_0), \forall R^-.C \in Label(w) \text{ and } \alpha : C \notin FullLabel(v)\}$
 - (c) $X := X \cup \{\alpha : \forall R^-.C \mid R \in CELabelR(w_0), trans_{\mathcal{R}}(R), \forall R^-.C \in Label(w) \text{ and } \alpha : \forall R^-.C \notin FullLabel(v)\}$
3. if $X \neq \emptyset$ then set $FmlsRC(v) := X$ and $Status(v) := \text{incomplete}$.

Explanation 5 Assume that the considered knowledge base is satisfiable and has a model $\mathcal{I}$ that satisfies $Label(v)$. Consider the following cases:

- Case v is a simple state and $\alpha = \text{null}$: Thus, v corresponds to an unnamed individual $y_v \in \Delta^{\mathcal{I}}$, while w corresponds to an R -successor y_w of y_v in $\mathcal{I}$. If $\forall R^-.C \in Label(w)$ then: $y_w \in (\forall R^-.C)^{\mathcal{I}}$ and hence $y_v \in C^{\mathcal{I}}$, and for that reason we want to have C in $FullLabel(v)$ as a requirement to be realized; so, if $C \notin FullLabel(v)$ then the status of v becomes **incomplete** and we add C into $FmlsRC(v)$ as a concept required for v for converse compatibility. If $\forall R^-.C \in Label(w)$ and R is a transitive role then: R^- is also transitive and we also have $y_v \in (\forall R^-.C)^{\mathcal{I}}$; so, analogously, if $\forall R^-.C \notin FullLabel(v)$ then the status of v becomes **incomplete** and we add $\forall R^-.C$ into $FmlsRC(v)$.
- Case v is a complex state and $\alpha = a$: Thus, v corresponds to an ABox with that individual a . The node w corresponds to an R -successor y_w of $a^{\mathcal{I}}$ in $\mathcal{I}$. If $\forall R^-.C \in Label(w)$ then: $y_w \in (\forall R^-.C)^{\mathcal{I}}$ and hence $a^{\mathcal{I}} \in C^{\mathcal{I}}$, and for that reason we want to have $a : C$ in $FullLabel(v)$ as a requirement to be realized; so, if $a : C \notin FullLabel(v)$ then the status of v becomes **incomplete** and we add $a : C$ into $FmlsRC(v)$ as an assertion required for v for converse compatibility. If $a : (\forall R^-.C) \in Label(w)$ and R is a transitive role then: R^- is also transitive and we also have $a^{\mathcal{I}} \in (\forall R^-.C)^{\mathcal{I}}$; so, analogously, if $a : (\forall R^-.C) \notin FullLabel(v)$ then the status of v becomes **incomplete** and we add $a : (\forall R^-.C)$ into $FmlsRC(v)$. $\square$

(**KCC**₃) If $Type(u) = \text{state}$, v_0 is a successor of u with $CELabelI(v_0) = \alpha$ and $R \in CELabelR(v_0)$, and v is a node in the local graph of v_0 with $\forall R^-.C \in Label(v)$ and $Status(v) \neq \text{closed}$ then

1. if $\alpha : \overline{C} \in FullLabel(u)$ then $Status(v) := \text{closed}$
2. else if $trans_{\mathcal{R}}(R)$ and $\alpha : \exists R^-. \overline{C} \in FullLabel(u)$ then $Status(v) := \text{closed}$
3. else if $(\alpha : C) \notin FullLabel(u)$ and $Status(u) \in \{\text{p-expanded, f-expanded}\}$ then $Status(u) := \text{incomplete}$ and $FmlFB(u) := (\alpha : C)$
4. else if $trans_{\mathcal{R}}(R)$ and $(\alpha : \forall R^-.C) \notin FullLabel(u)$ and $Status(u) \in \{\text{p-expanded, f-expanded}\}$ then set $Status(u) := \text{incomplete}$ and $FmlFB(u) := (\alpha : \forall R^-.C)$.

Explanation 6 Assume that the considered knowledge base is satisfiable and has a model $\mathcal{I}$ that satisfies $Label(u)$. We consider here only the case when u is a simple state and $\alpha = \text{null}$. (The case when u is a complex state and α is a named individual is similar, cf. Explanation 5.) Thus, u corresponds to an unnamed individual $y_u \in \Delta^{\mathcal{I}}$. In the constructed tableau, there is an expansion path from u via v_0 to v . The question is: whether that expansion path should be taken into account, and if we should consider that expansion path, what should be done for converse compatibility. Note that: if $CELabelT(v_0) = \text{checkingFeasibility}$ and $(x_{v_0} = 0) \in ILConstraints(u)$ then v_0 is not used for the construction of $\mathcal{I}$; and if the path from v_0 to v uses some non-unary static expansions then v is just one of possible “expansions” of v_0 .

- If v corresponds to an R -successor y_v of y_u in $\mathcal{I}$ then $y_v \in (\forall R^-.C)^{\mathcal{I}}$ (since $\forall R^-.C \in Label(v)$) and hence $y_u \in C^{\mathcal{I}}$, which means we should require $C \in FullLabel(u)$. So, if $\overline{C} \in FullLabel(u)$ then the expansion path from u via v_0 to v cannot be used and we set $Status(v) := \text{closed}$ to mark that v cannot be used to realize the requirements of u .

- If R is a transitive role and v corresponds to an R -successor y_v of y_u in $\mathcal{I}$ then we also have $y_u \in (\forall R^-.C)^{\mathcal{I}}$, which means we should require $\forall R^-.C \in \text{FullLabel}(u)$. So, if R is transitive and $\exists R^-.C \in \text{FullLabel}(u)$ (note that $\exists R^-.C$ is the negation of $\forall R^-.C$) then the expansion path from u via v_0 to v cannot be used and we set $\text{Status}(v) := \text{closed}$ to mark that v cannot be used to realize the requirements of u .
- In the other case, if $\forall R^-.C \in \text{Label}(v)$ and $\{C, \overline{C}\} \cap \text{FullLabel}(u) = \emptyset$ then we would like to have either C or $\overline{C}$ in $\text{Label}(u)$ and therefore set $\text{Status}(u) := \text{incomplete}$ and $\text{FmlFB}(u) := C$ (as a concept for branching on at u).
- In the other case, if R is transitive, $\forall R^-.C \in \text{Label}(v)$ and $\{\forall R^-.C, \exists R^-.C\} \cap \text{FullLabel}(u) = \emptyset$ then we would like to have either $\forall R^-.C$ or $\exists R^-.C$ in $\text{Label}(u)$ and therefore set $\text{Status}(u) := \text{incomplete}$ and $\text{FmlFB}(u) := \forall R^-.C$ (as a concept for branching on at u). $\square$

(KCC₄) If u is a state with $\text{Status}(u) \in \{\text{p-expanded}, \text{f-expanded}\}$, v_0 is a successor of u with $\text{CELabel}(v_0) = \alpha$ and $R \in \text{CELabelR}(v_0)$, v is a node in the local graph of v_0 such that $\text{Status}(v) \neq \text{closed}$ and

- either $\text{Label}(v)$ contains $\leq n R^-.C$,
- or $\text{Label}(v)$ contains $\geq n R^-.C$ or $\exists R^-.C$, where R is a numeric role,

and $\{(\alpha:C), (\alpha:\overline{C})\} \cap \text{FullLabel}(u) = \emptyset$

then set $\text{Status}(u) := \text{incomplete}$ and $\text{FmlFB}(u) := (\alpha:C)$.

Explanation 7 This rule deals with the case when there lacks information at u for deciding how to satisfy the number restrictions of v . We want to have either $\alpha:C$ or $\alpha:\overline{C}$ in $\text{FullLabel}(u)$. So, we set $\text{Status}(u) := \text{incomplete}$ and $\text{FmlFB}(u) := (\alpha:C)$ (as a formula for branching on at u). $\square$

(KCC₅) If u is a state with $\text{Status}(u) = \text{f-expanded}$, v_0 is a successor of u with $\text{CELabelT}(v_0) = \text{checkingFeasibility}$, $R \in \text{CELabelR}(v_0)$ and $\text{CELabel}(v_0) = \alpha$, and v is a node in the local graph of v_0 such that

- $\text{Status}(v) \neq \text{closed}$, $\text{Label}(v)$ contains $\leq m R^-.C$ as well as $\geq n S^-.D$ or $\exists S^-.D$,
- $S \sqsubseteq_{\mathcal{R}} R$, $S \notin \text{CELabelR}(v_0)$, $\alpha:C \in \text{FullLabel}(u)$, $\alpha:\overline{D} \notin \text{FullLabel}(u)$,
- $\{(\alpha:\exists S.\top_R), (\alpha:\forall S.\perp)\} \cap \text{Label}(u) = \emptyset$

then set $\text{Status}(u) := \text{incomplete}$ and $\text{FmlFB}(u) := (\alpha:\exists S.\top_R)$.

(Here, $\top_R$ is $\top$ annotated by R . Semantically, $\top_R$ is equivalent to $\top$, i.e., $\top_R^{\mathcal{I}} = \top^{\mathcal{I}} = \Delta^{\mathcal{I}}$ for every interpretation $\mathcal{I}$. Besides, let $\overline{\top_R} = \perp$ and hence $\overline{\exists S.\top_R} = \forall S.\perp$.)

Explanation 8 Assume that $\text{Label}(v)$ contains φ which is either $\geq n S^-.D$ (with $n \geq 1$) or $\exists S^-.D$. To realize the requirement φ at v we want to know whether u can be used for that purpose. That is, we want $(S \in \text{CELabelR}(v_0) \text{ and } \alpha:D \in \text{FullLabel}(u))$ or $S \notin \text{CELabelR}(v_0) \text{ and } \alpha:\overline{D} \in \text{FullLabel}(u)$. If $S \in \text{CELabelR}(v_0)$ then the will to have either $\alpha:D$ or $\alpha:\overline{D}$ in $\text{FullLabel}(u)$ can be realized by the rule (KCC₄). If $\alpha:\overline{D} \in \text{FullLabel}(u)$ then u cannot be used to realize the requirement φ at v . Consider the case when $S \notin \text{CELabelR}(v_0)$ and $\alpha:\overline{D} \notin \text{FullLabel}(u)$. If v was treated as a state then to realize the requirement φ at v we would create an S^- -successor w of v and put D to $\text{Label}(w)$. As $S \sqsubseteq_{\mathcal{R}} R$, the node w is also an R^- -successor of v . Since $\leq m R^-.C \in \text{Label}(v)$ and $\alpha:C \in \text{FullLabel}(u)$, there may be the need to merge w to u . Such merging would add S into $\text{CELabelR}(v_0)$. However, our method does not merge nodes explicitly. Roughly speaking, we want to decide whether to add S into $\text{CELabelR}(v_0)$ or not. To solve the problem, we set $\text{Status}(u) := \text{incomplete}$ and $\text{FmlFB}(u) := (\alpha:\exists S.\top_R)$. Later, if a state u' is a “completion” of u , then either $\alpha:\exists S.\top_R \in \text{Label}(u')$ or $\alpha:\forall S.\perp \in \text{Label}(u')$. If $\alpha:\forall S.\perp \in \text{Label}(u')$ then u' will not have any S -successor. If $\alpha:\exists S.\top_R \in \text{Label}(u')$ then u' will have some S -successor v' with $\top_R \in \text{Label}(v')$, and the occurrence of $\top_R$ in $\text{Label}(v')$ guarantees that the possibility of merging v' to any R -successor of u' will be considered by the transitional full-expansion rule. $\square$

The Non-unary Static Expansion Rule:

(NUS) If $Type(v) = \text{non-state}$ and $Status(v) = \text{unexpanded}$ then

1. if $\alpha : (C \sqcup D) \in Label(v)$ and $\{\alpha : C, \alpha : D\} \cap FullLabel(v) = \emptyset$ then
 - (a) let $X = Label(v) - \{\alpha : (C \sqcup D)\}$
 - (b) let $Y = RFmls(v) \cup \{\alpha : (C \sqcup D)\}$
 - (c) $ConToSucc(v, \text{non-state}, \text{complex}, X \cup \{\alpha : C\}, Y, \text{null})$
 - (d) $ConToSucc(v, \text{non-state}, \text{complex}, X \cup \{\alpha : D\}, Y, \text{null})$
 - (e) $Status(v) := \text{f-expanded}$

Explanation 9 This subrule deals with syntactic branching on $\alpha : (C \sqcup D) \in Label(v)$. We expand v by connecting it to two successors w_1 and w_2 , whose labels are the label of v with $\alpha : (C \sqcup D)$ replaced by $\alpha : C$ or $\alpha : D$, respectively. The formula $\alpha : (C \sqcup D)$ is put into both $RFmls(w_1)$ and $RFmls(w_2)$. The expansion is done only when both w_1 and w_2 have a larger $FullLabel$ than v . $\square$

2. else if $SType(v) = \text{complex}$, $R(a, b) \in Label(v)$ and
 - either $Label(v)$ contains $a : (\leq n R.C)$,
 - or $Label(v)$ contains $a : (\geq n R.C)$ or $a : (\exists R.C)$, where R is a numeric role, and $\{b : C, b : \overline{C}\} \cap FullLabel(v) = \emptyset$ then
 - (a) $ConToSucc(v, \text{non-state}, \text{complex}, Label(v) \cup \{b : C\}, RFmls(v), \text{null})$
 - (b) $ConToSucc(v, \text{non-state}, \text{complex}, Label(v) \cup \{b : \overline{C}\}, RFmls(v), \text{null})$
 - (c) $Status(v) := \text{f-expanded}$

Explanation 10 This subrule deals with the case when there lacks information about b for deciding how to satisfy the number restrictions about a (cf. Explanation 7). We want to have either $b : C$ or $b : \overline{C}$ in $FullLabel(v)$. So, we expand v by semantic branching: we connect it to two successors, one with label $Label(v) \cup \{b : C\}$ and the other with label $Label(v) \cup \{b : \overline{C}\}$. The expansion is done only when both the successors have a larger $FullLabel$ than v . $\square$

3. else if $SType(v) = \text{complex}$, $\{a : (\leq n R.C), R(a, b), R(a, b'), b : C, b' : C\} \subseteq FullLabel(v)$, $b \neq b'$ and $\{b \neq b', b' \neq b\} \cap Label(v) = \emptyset$ then
 - (a) let X be the set obtained from $Label(v)$ by replacing every occurrence of b' by b
 - (b) let Y be the set obtained from $RFmls(v)$ by replacing every occurrence of b' not in $\doteq$ expressions by b
 - (c) $ConToSucc(v, \text{non-state}, \text{complex}, X, Y \cup \{b \doteq b'\}, \text{null})$
 - (d) $ConToSucc(v, \text{non-state}, \text{complex}, Label(v) \cup \{b \neq b'\}, RFmls(v), \text{null})$
 - (e) $Status(v) := \text{f-expanded}$

Explanation 11 This subrule deals with the case when there lacks information about whether b and b' denote the same individual for deciding how to satisfy the number restrictions about a . We expand v by semantic branching: either b and b' denote the same individual or they do not. Technically, we connect v to two successors with appropriate contents. The presence of $b \doteq b'$ at the step 3c is just for making the proofs easier and is not needed for correctness and completeness of our C_{SHIQ} calculus. $\square$

4. else if $SType(v) = \text{complex}$, $\{a : (\leq m R.C), R(a, b)\} \subseteq Label(v)$, $Label(v)$ contains $a : (\geq n S.D)$ or $a : \exists S.D$ with $S \sqsubseteq_{\mathcal{R}} R$, and $\{S(a, b), \neg S(a, b)\} \cap FullLabel(v) = \emptyset$ then
 - (a) $ConToSucc(v, \text{non-state}, \text{complex}, Label(v) \cup \{S(a, b)\}, RFmls(v), \text{null})$
 - (b) $ConToSucc(v, \text{non-state}, \text{complex}, Label(v), RFmls(v) \cup \{\neg S(a, b)\}, \text{null})$
 - (c) $Status(v) := \text{f-expanded}$.

Explanation 12 This subrule deals with the case when there lacks information for deciding how to satisfy the number restrictions about a (cf. the rule (KCC₅) and Explanation 8). We want to decide whether b is an S -successor of a or not. So, we expand v by semantic branching: we connect it to two successors, one with label containing $S(a, b)$ and the other with $RFmls$ containing $\neg S(a, a)$. The expansion is done only when both the successors have a larger $FullLabel$ than v . $\square$

The Forming-state Rule:

- (FS₁) If $Type(v) = \text{non-state}$, $SType(v) = \text{simple}$ and $Status(v) = \text{unexpanded}$ then
1. let $u = StatePred(v)$, $v_0 = ATPred(v)$ and $\alpha = CELabelI(v_0)$
 2. set $X := Label(v)$
 3. for each $(\leq n R.D) \in Label(v)$ do
 - (a) if $R^- \in CELabelR(v_0)$ and $(\alpha:D) \in FullLabel(u)$ then add $\preceq(n-1) R.D$ into X
 - (b) else add $\preceq n R.D$ into X
 4. for each $(\geq n R.D) \in Label(v)$ with $n \geq 2$ do
 - (a) if $R^- \in CELabelR(v_0)$ and $(\alpha:D) \in FullLabel(u)$ then add $\succeq(n-1) R.D$ into X
 - (b) else add $\succeq n R.D$ into X
 5. for each $(\geq 1 R.D)$ or $\exists R.D$ from $Label(v)$, where R is a numeric role, do
 - (a) if $R^- \notin CELabelR(v_0)$ or $(\alpha:D) \notin FullLabel(u)$ then add $\succeq 1 R.D$ into X
 6. $ConToSucc(v, \text{state}, \text{simple}, X, RFmls(v), \text{null})$
 7. $Status(v) := \text{f-expanded}$.

Explanation 13 When the rules (UPS), (US) and (KCC) are not applicable (to any node) and the rule (NUS) is not applicable to v , we apply this forming-state rule to v by connecting it to a simple state w . Assume that the considered knowledge base is satisfiable and has a model $\mathcal{I}$ such that the nodes v and w are used for the construction of $\mathcal{I}$. In the constructed graph, such a state w is globally cached and may have many predecessors. However, the elements y_w of the domain of $\mathcal{I}$ that correspond to w are nodes in disjoint trees (cf. Remark 3.2), and each of them has only one predecessor y_u , which corresponds to u . When computing contents for w we put into $Label(w)$ the requirements from $Label(v)$ after an appropriate modification that takes into account the relationship between y_w and y_u , i.e., the relationship between v and u via v_0 . For example, if $(\leq n R.D) \in Label(v)$, $R^- \in CELabelR(v_0)$ and $(\alpha:D) \in FullLabel(u)$ then $y_w \in \Delta^{\mathcal{I}}$ (which corresponds to all w, v, v_0) already has the R -successor $y_u \in D^{\mathcal{I}}$, and we have to guarantee only that y_w has $n-1$ other R -successors satisfying D (i.e., belonging to $D^{\mathcal{I}}$), and that is why we add into $Label(w)$ the requirement $\preceq(n-1) R.D$. Notice the use of $\preceq$ instead of $\leq$. Also note that we can assume $Status(u) \neq \text{incomplete}$ (otherwise, there is no sense for expanding v) and, as the rule for keeping converse compatibility is not applicable, in that case either $\alpha:D$ or $\alpha:\bar{D}$ belongs to $FullLabel(u)$. $\square$

- (FS₂) If $Type(v) = \text{non-state}$, $SType(v) = \text{complex}$ and $Status(v) = \text{unexpanded}$ then
1. set $X := Label(v)$
 2. for each $a:(\leq n R.D) \in Label(v)$ do
 - (a) let $m = \#\{b \mid \{R(a, b), b:D\} \subseteq FullLabel(v)\}$
 - (b) add $a:(\preceq(n-m) R.D)$ into X
 3. for each $(a:C) \in Label(v)$, where C is $\geq n R.D$ or $\exists R.D$ and R is a numeric role, do
 - (a) if $C = \exists R.D$ then let $n = 1$
 - (b) let $m = \#\{b \mid \{R(a, b), b:D\} \subseteq FullLabel(v)\}$
 - (c) if $n > m$ then add $a:(\succeq(n-m) R.D)$ into X
 4. $ConToSucc(v, \text{state}, \text{complex}, X, RFmls(v), \text{null})$
 5. $Status(v) := \text{f-expanded}$.

Explanation 14 When the rules (UPS), (US), (KCC) and (NUS) are not applicable to the complex non-state v , we apply this forming-state rule to v by connecting it to a complex state w . When computing contents for w we put into $Label(w)$ the requirements from $Label(v)$ after an appropriate modification that takes into account the assertions in $Label(v)$ that represent the relationship between named individuals. For example, if $a:(\leq n R.D) \in Label(v)$ and there are m pairwise different individuals $b_1, \dots, b_m$ such that $\{R(a, b_i), b_i:D \mid 1 \leq i \leq m\} \subseteq FullLabel(v)$ then we add into $Label(w)$ the requirements $a:(\preceq(n-m) R.D)$. Notice the use

of $\preceq$ instead of $\leq$. Note that, since the rule (NUS) is not applicable to v , we must have that $(b_i \neq b_j) \in \text{Label}(v)$ for any pair $i \neq j$, and for any individual b such that $R(a, b) \in \text{Label}(v)$, either $b : D$ or $b : \overline{D}$ must belong to $\text{FullLabel}(v)$. When expanding w we will not have to pay attention to the relationship between the individuals occurring in $\text{Label}(w)$. $\square$

The Transitional Partial-Expansion Rule:

- (TP) If $\text{Type}(v) = \text{state}$ and $\text{Status}(v) = \text{unexpanded}$ then
1. for each $(\alpha : \exists R.D) \in \text{Label}(v)$, where R is a non-numeric role, do
 - (a) $X := \{D\} \cup \{D' \mid \alpha : \forall R.D' \in \text{Label}(v)\} \cup \{\forall S.D' \mid \alpha : \forall S.D' \in \text{Label}(v), R \sqsubseteq_{\mathcal{R}} S \text{ and } \text{trans}_{\mathcal{R}}(S)\} \cup \mathcal{T}$
 - (b) $\text{ceLabel} := \langle \text{testingClosedness}, \{S \mid R \sqsubseteq_{\mathcal{R}} S\}, \alpha \rangle$
 - (c) $\text{NewSucc}(v, \text{non-state}, \text{simple}, X, \emptyset, \text{ceLabel})$
 2. $\text{Status}(v) := \text{p-expanded}$.

Explanation 15 To realize a requirement $\alpha : \exists R.D$ at v , where R is a non-numeric role, we connect v to a new simple non-state w with appropriate contents as shown in the rule. $\square$

The Transitional Full-Expansion Rule:

- (TF) If $\text{Type}(v) = \text{state}$ and $\text{Status}(v) = \text{p-expanded}$ then
1. $\mathcal{E} := \emptyset, \mathcal{E}' := \emptyset$
 2. for each $(\alpha : \succeq n R.D) \in \text{Label}(v)$ do
 - (a) $X := \{S \mid R \sqsubseteq_{\mathcal{R}} S\}$
 - (b) $Y := \{D\} \cup \{D' \mid \alpha : \forall R.D' \in \text{Label}(v)\} \cup \{\forall S.D' \mid \alpha : \forall S.D' \in \text{Label}(v), R \sqsubseteq_{\mathcal{R}} S \text{ and } \text{trans}_{\mathcal{R}}(S)\} \cup \mathcal{T}$
 - (c) $\mathcal{E} := \mathcal{E} \cup \{\langle X, Y, \alpha \rangle\}$
 3. for each $\alpha : (\preceq n R.C) \in \text{Label}(v)$ do
 - (a) for each $\langle X, Y, \alpha \rangle \in \mathcal{E}$ do
 - i. if $R \in X$ and $\{C, \overline{C}\} \cap Y = \emptyset$ then $\mathcal{E}' := \mathcal{E}' \cup \{\langle X, Y \cup \{C\}, \alpha \rangle, \langle X, Y \cup \{\overline{C}\}, \alpha \rangle\}$ (i.e., $\langle X, Y, \alpha \rangle$ is replaced by $\langle X, Y \cup \{C\}, \alpha \rangle$ and $\langle X, Y \cup \{\overline{C}\}, \alpha \rangle$)
 - ii. else $\mathcal{E}' := \mathcal{E}' \cup \{\langle X, Y, \alpha \rangle\}$
 - (b) $\mathcal{E} := \mathcal{E}', \mathcal{E}' := \emptyset$
 4. repeat
 - (a) for each $\alpha : (\preceq n R.C) \in \text{Label}(v), \langle X, Y, \alpha \rangle \in \mathcal{E}$ and $\langle X', Y', \alpha \rangle \in \mathcal{E}$ such that $R \in X, C \in Y, R \in X', C \in Y', \langle X \cup X', Y \cup Y', \alpha \rangle \notin \mathcal{E}$ and $Y \cup Y'$ does not contain any pair of the form $\varphi, \overline{\varphi}$ do add $\langle X \cup X', Y \cup Y', \alpha \rangle$ into $\mathcal{E}$ (i.e., the merger of $\langle X, Y, \alpha \rangle$ and $\langle X', Y', \alpha \rangle$ is added into $\mathcal{E}$)
 - (b) for each $\langle X, Y, \alpha \rangle \in \mathcal{E}, \langle X', Y', \alpha \rangle \in \mathcal{E}$ and $R \in X \cap X'$ such that $\top_R \in Y \cup Y', \langle X \cup X', Y \cup Y', \alpha \rangle \notin \mathcal{E}$ and $Y \cup Y'$ does not contain any pair of the form $\varphi, \overline{\varphi}$ do add $\langle X \cup X', Y \cup Y', \alpha \rangle$ into $\mathcal{E}$
 until no tuples were added into $\mathcal{E}$ during the last iteration
 5. for each $\langle X, Y, \alpha \rangle \in \mathcal{E}$ do
 - (a) $\text{NewSucc}(v, \text{non-state}, \text{simple}, Y, \emptyset, \langle \text{checkingFeasibility}, X, \alpha \rangle)$
 6. let $W = \{w \mid \langle v, w \rangle \in E \text{ and } \text{CELabelI}(w) = \text{checkingFeasibility}\}$
 7. $\text{ILConstraints}(v) := \{x_w \geq 0 \mid w \in W\}$
 8. for each $(\alpha : C) \in \text{Label}(v)$ do
 - (a) if C is of the form $\succeq n R.D$ then add into $\text{ILConstraints}(v)$ the constraint $\sum \{x_w \mid w \in W, \text{CELabelI}(w) = \alpha, R \in \text{CELabelR}(w), D \in \text{Label}(w)\} \geq n$
 - (b) if C is of the form $\preceq n R.D$ then add into $\text{ILConstraints}(v)$ the constraint $\sum \{x_w \mid w \in W, \text{CELabelI}(w) = \alpha, R \in \text{CELabelR}(w), D \in \text{Label}(w)\} \leq n$
 9. $\text{Status}(v) := \text{f-expanded}$.

Explanation 16 To satisfy a requirement $\varphi = (\alpha : \succeq n R.C) \in \text{Label}(v)$, one can first create a successor w_φ of v specified by the tuple $\langle X, Y, \alpha \rangle$ computed at the step 2, where X presents $\text{CELabel}R(w_\varphi)$, Y presents $\text{Label}(w_\varphi)$ and α presents $\text{CELabel}I(w_\varphi)$, and then clone w_φ to create n successors for v (or only record the intention somehow). The label of w_φ contains only formulas necessary for realizing the requirement $\alpha : \exists R.C$ and related ones of the form $\alpha : \forall R'.C'$ at v . To satisfy requirements of the form $\alpha : \preceq n' R'.C'$ at v , where $R \sqsubseteq_{\mathcal{R}} R'$, we tend to use only copies of w_φ extended with either C' or $\overline{C'}$ (for easy counting) as well as the mergers of such extended nodes. So, we first start with the set $\mathcal{E}$ constructed at the step 2, which consists of tuples with information about successors to be created for v . We then modify $\mathcal{E}$ by taking necessary extensions of the nodes (see the step 3). After that we continue modifying $\mathcal{E}$ by adding to it also appropriate mergers of nodes (see the step 4). The merging specified at the step 4b corresponds to the rule (KCC₅) with Explanation 8. Successors for v are created at the step 5. The number of copies of a node w that are intended to be used as successors of v is represented by a variable x_w (we will not actually create such copies). The set $\text{ILConstraints}(v)$ consisting of appropriate constraints about such variables are set at the steps 6-8. $\square$

3.4 Properties of C_{SHIQ} -Tableaux

Define the size of a knowledge base $KB = \langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ to be the number of bits used for the usual sequential representation of KB . It is greater than the number of symbols occurring in KB . If N is the size of KB and $\leq n R.C$ or $\geq n R.C$ is a number restriction occurring in KB then $n \leq 2^N$.

Lemma 3.6. *Let $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ be a knowledge base in NNF of the logic SHIQ and let N be the size of $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$. Then a C_{SHIQ} -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ can be constructed in (at most) exponential time in N .* $\square$

Theorem 3.7 (Soundness and Completeness). *Let $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ be a knowledge base in NNF of the logic SHIQ and $G = \langle V, E, \nu \rangle$ be an arbitrary C_{SHIQ} -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$. Then $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ is satisfiable iff $\text{Status}(\nu) \neq \text{closed}$.* $\square$

See the next section for the proofs of the above lemma and theorem.

To check satisfiability of $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ one can construct a C_{SHIQ} -tableau for it, then return “no” when the root of the tableau has status closed, or “yes” in the other case. We call this the C_{SHIQ} -tableau decision procedure. The corollary given below immediately follows from Theorem 3.7 and Lemma 3.6.

Corollary 3.8. *The C_{SHIQ} -tableau decision procedure has EXPTIME complexity.* $\square$

4 Proofs

4.1 Complexity

Define $\text{closure}(\mathcal{R}, \mathcal{T}, \mathcal{A})$ to be the smallest set Γ of formulas such that:

- all concepts (and subconcepts) used in $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ belong to Γ ,
- if R, S are numeric roles and $S \sqsubseteq_{\mathcal{R}} R$ then $\exists S.\top_R, \forall S.\perp, \top_R$ and $\perp$ belong to Γ ,
- if $\forall S.C \in \Gamma$ and $R \sqsubseteq_{\mathcal{R}} S$ then $\forall R.C \in \Gamma$,
- if $\leq 0 R.C \in \Gamma$ then $\forall R.\overline{C} \in \Gamma$,
- if $\overline{C} \in \Gamma$ and C is not of the form $\preceq n R.C$ nor $\succeq n R.C$ then $\overline{C} \in \Gamma$,
- if $\exists R.C \in \Gamma$ and R is a numeric role then $\succeq 1 R.C \in \Gamma$,
- if $\geq n R.C \in \Gamma$ and $0 \leq m < n$ then $\succeq (n - m) R.C \in \Gamma$,
- if $\leq n R.C \in \Gamma$ and $0 \leq m \leq n$ then $\preceq (n - m) R.C \in \Gamma$,
- all assertions of $\mathcal{A}$ belong to Γ ,

- if $C \in \Gamma$ and a is an individual occurring in Γ then $a:C \in \Gamma$,
- if b and b' are individuals occurring in Γ then $b \doteq b'$ and $b \not\doteq b'$ belong to Γ ,
- if $R(a, b) \in \Gamma$ then $R^-(b, a)$ and $\neg R(a, b)$ belong to Γ ,
- if $R(a, b) \in \Gamma$ and $R \sqsubseteq_{\mathcal{R}} S$ then $S(a, b) \in \Gamma$,
- if $R(a, b) \in \Gamma$ and $S \sqsubseteq_{\mathcal{R}} R$ then $S(a, b) \in \Gamma$.

Lemma 4.1. *The number of formulas of $\text{closure}(\mathcal{R}, \mathcal{T}, \mathcal{A})$ is of rank $O(\mathbf{N}^3)$, where $\mathbf{N}$ is the size of $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$.* $\square$

The proof of this lemma is straightforward.

We recall below Lemma 3.6 before presenting its proof.

Lemma 3.6. *Let $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ be a knowledge base in NNF of the logic $\mathcal{SHIQ}$ and let $\mathbf{N}$ be the size of $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$. Then a $C_{\mathcal{SHIQ}}$ -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ can be constructed in (at most) exponential time in $\mathbf{N}$.*

Proof. Let's construct any $C_{\mathcal{SHIQ}}$ -tableau $G = \langle V, E, \nu \rangle$ for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$.

Let $\mathbf{N}'$ be the number of formulas of $\text{closure}(\mathcal{R}, \mathcal{T}, \mathcal{A})$. We have $\mathbf{N}' = O(\mathbf{N}^3)$. For each $v \in V$, $\text{Label}(v) \subseteq \text{closure}(\mathcal{R}, \mathcal{T}, \mathcal{A})$. Since states of G are cached, it follows that G has no more than $2^{\mathbf{N}'}$ states. Each state has no more than $O(2^{\mathbf{N}} \cdot 2^{\mathbf{N}'} \cdot \mathbf{N})$ successors. If v is a successor of a state, then nodes in the local graph of v are cached and hence there are no more than $2^{\mathbf{N}'}$ of them. Therefore, G has $O(2^{f(\mathbf{N})})$ nodes, where $f(\mathbf{N})$ is a polynomial of $\mathbf{N}$.

Checking feasibility of $IL\text{Constraints}(v)$ for a state v is an $\text{IFDL}(\mathbf{N}, 2^{\mathbf{N}} \cdot 2^{\mathbf{N}'} \cdot \mathbf{N}, \mathbf{N})$ -problem, and by Lemma 2.1, can be solved in (at most) exponential time in $\mathbf{N}$. Thus, checking whether a rule is applicable and applying a rule can be done in time $O(2^{g(\mathbf{N})})$, where $g(\mathbf{N})$ is a polynomial of $\mathbf{N}$.

Choosing a node to expand can be done in polynomial time in the size of the graph. As each node is re-expanded at most once (for converse compatibility), we conclude that the graph G can be constructed in (at most) exponential time in $\mathbf{N}$. $\square$

4.2 Soundness

Lemma 4.2. *Let $G = \langle V, E, \nu \rangle$ be a $C_{\mathcal{SHIQ}}$ -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$. Then, for every simple node $v \in V$, $\text{FullLabel}(v)$ is equivalent to $\text{Label}(v)$. That is, for any interpretation $\mathcal{I}$, $(\text{FullLabel}(v))^{\mathcal{I}} = (\text{Label}(v))^{\mathcal{I}}$.* $\square$

The proof of this lemma is straightforward.

Let G be a $C_{\mathcal{SHIQ}}$ -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$. For each node v of G with $\text{Status}(v) \in \{\text{incomplete}, \text{closed}, \text{open}\}$, let $\text{DSTimeStamp}(v)$ be the moment at which $\text{Status}(v)$ was changed to its final value (i.e., determined to be incomplete, closed or open). DSTimeStamp stands for “determined-status time-stamp”. For each non-state v of G , let $\text{ETimeStamp}(v)$ be the moment at which v was expanded the last time.⁴

For a simple non-state v with $\text{AfterTrans}(v) = \text{true}$, $\text{StatePred}(v) = u$ and $\text{CELabel}(v) = \alpha$, we define $\text{CEFullLabelR}(v)$ to be $\text{CELabelR}(v)$ extended with all $\neg S$ such that:

- $S \notin \text{CELabelR}(v)$ and $S \sqsubseteq_{\mathcal{R}} R$ for some $R \in \text{CELabelR}(v)$,
- some node w in the local graph of v has $\text{Label}(w)$ containing $\leq m R^-.C$ as well as $\exists S^-.D$ or $\geq n S^-.D$ with $n > 0$,
- $\alpha:C \in \text{FullLabel}(u)$ and $\alpha:\bar{D} \notin \text{FullLabel}(u)$.

For $X = \{\alpha:C_1, \dots, \alpha:C_n\}$, let $\text{Cnj}(X) = \alpha:(C_1 \sqcap \dots \sqcap C_n)$.

Lemma 4.3. *Let $G = \langle V, E, \nu \rangle$ be a $C_{\mathcal{SHIQ}}$ -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$. For every $v \in V$:*

⁴ Each non-state may be re-expanded at most once (for making converse compatibility) and each state is expanded at most once.

1. if $Status(v) = \text{closed}$ then
 - (a) case $Type(v) = \text{state}$ and $SType(v) = \text{simple}$: for any predecessor u of v and for $u_0 = StatePred(u)$, $u_1 = ATPred(u)$, we have that:
 - i. if $Status(u_0) \neq \text{incomplete}$ and $SType(u_0) = \text{simple}$ then there do not exist any model $\mathcal{I}$ of both $\mathcal{R}$ and $\mathcal{T}$ and any elements $x, y \in \Delta^{\mathcal{I}}$ such that $x \in (FullLabel(u_0))^{\mathcal{I}}$, $y \in (Label(v))^{\mathcal{I}}$, $\langle x, y \rangle \in R^{\mathcal{I}}$ for all $R \in CELabelR(u_1)$, and $\langle x, y \rangle \notin R^{\mathcal{I}}$ for all $(\neg R) \in CEFullLabelR(u_1)$,
 - ii. if $Status(u_0) \neq \text{incomplete}$ and $SType(u_0) = \text{complex}$ then there do not exist any model $\mathcal{I}$ of $\langle \mathcal{R}, \mathcal{T}, FullLabel(u_0) \rangle$ and any element $y \in \Delta^{\mathcal{I}}$ such that: $y \in (Label(v))^{\mathcal{I}}$, and for $x = (CELabelI(u_1))^{\mathcal{I}}$, $\langle x, y \rangle \in R^{\mathcal{I}}$ for all $R \in CELabelR(u_1)$, and $\langle x, y \rangle \notin R^{\mathcal{I}}$ for all $(\neg R) \in CEFullLabelR(u_1)$,
 - (b) case $Type(v) = \text{state}$ and $SType(v) = \text{complex}$: $FullLabel(v)$ is unsatisfiable w.r.t. $\mathcal{R}$ and $\mathcal{T}$,
 - (c) case $Type(v) = \text{non-state}$ and $StatePred(v) = \text{null}$: $FullLabel(v)$ is unsatisfiable w.r.t. $\mathcal{R}$ and $\mathcal{T}$,
 - (d) case $Type(v) = \text{non-state}$, $u = StatePred(v) \neq \text{null}$ and $SType(u) = \text{simple}$: if $v_0 = ATPred(v)$ then there do not exist any model $\mathcal{I}$ of both $\mathcal{R}$ and $\mathcal{T}$ and any elements $x, y \in \Delta^{\mathcal{I}}$ such that $x \in (FullLabel(u))^{\mathcal{I}}$, $y \in (Label(v))^{\mathcal{I}}$, $\langle x, y \rangle \in R^{\mathcal{I}}$ for all $R \in CELabelR(v_0)$, and $\langle x, y \rangle \notin R^{\mathcal{I}}$ for all $(\neg R) \in CEFullLabelR(v_0)$,
 - (e) case $Type(v) = \text{non-state}$, $u = StatePred(v) \neq \text{null}$ and $SType(u) = \text{complex}$: if $v_0 = ATPred(v)$ then there do not exist any model $\mathcal{I}$ of $\langle \mathcal{R}, \mathcal{T}, FullLabel(u) \rangle$ and any element $y \in \Delta^{\mathcal{I}}$ such that: $y \in (Label(v))^{\mathcal{I}}$, and for $x = (CELabelI(v_0))^{\mathcal{I}}$, $\langle x, y \rangle \in R^{\mathcal{I}}$ for all $R \in CELabelR(v_0)$, and $\langle x, y \rangle \notin R^{\mathcal{I}}$ for all $(\neg R) \in CEFullLabelR(v_0)$,
2. if $Status(v) = \text{incomplete}$, $Type(v) = \text{state}$ and $FmlsRC(v) \neq \emptyset$ then $FullLabel(v) \cup \{\neg \text{Cnj}(FmlsRC(v))\}$ is unsatisfiable w.r.t. $\mathcal{R}$ and $\mathcal{T}$,
3. if $Type(v) = \text{non-state}$ and $w_1, \dots, w_k$ are all the successors of v then, for every model $\mathcal{I}$ of $\mathcal{R}$ and every $x \in \Delta^{\mathcal{I}}$,
 - (a) case $SType(v) = \text{simple}$: $x \in (FullLabel(v))^{\mathcal{I}}$ iff there exists $1 \leq i \leq k$ such that $x \in (FullLabel(w_i))^{\mathcal{I}}$,
 - (b) case $SType(v) = \text{complex}$: $\mathcal{I}$ is a model of $FullLabel(v)$ iff there exists $1 \leq i \leq k$ such that $\mathcal{I}$ is a model of $FullLabel(w_i)$.

Proof. We prove this lemma by induction on both $DSTimeStamp(v)$ and $ETimeStamp(v)$.

Consider the case 1(a)i when v gets status closed because $ILConstraints(v)$ is infeasible. For this case, we prove the contrapositive. Suppose that:

$$\begin{aligned}
 &Type(v) = \text{state}, SType(v) = \text{simple}, \langle u, v \rangle \in E, u_0 = StatePred(u), u_1 = \\
 &ATPred(u), Status(u_0) \neq \text{incomplete}, SType(u_0) = \text{simple}, \mathcal{I} \text{ is a model of both } \mathcal{R} \text{ and } \mathcal{T}, \\
 &x \in (FullLabel(u_0))^{\mathcal{I}}, y \in (Label(v))^{\mathcal{I}}, \langle x, y \rangle \in R^{\mathcal{I}} \text{ for all } R \in CELabelR(u_1), \text{ and } \langle x, y \rangle \notin R^{\mathcal{I}} \text{ for all } (\neg R) \in CEFullLabelR(u_1).
 \end{aligned} \tag{1}$$

We show that $ILConstraints(v)$ is feasible. Without loss of generality, assume that $\mathcal{I}$ is finitely-branching. Thus, the set $Z = \{z \in \Delta^{\mathcal{I}} \mid z \neq x, \langle y, z \rangle \in R^{\mathcal{I}} \text{ for some } R \in \mathbf{R} \cup \mathbf{R}^-\}$ is finite. Let us compute a solution $\mathcal{S}$ for $ILConstraints(v)$ as follows.

1. For each successor w of v , set $n_w := 0$.
2. For each $z \in Z$ do:
 - (a) let $w_1, \dots, w_k$ be all the successors of v such that, for each $1 \leq i \leq k$:
 - i. $CELabelT(w_i) = \text{checkingFeasibility}$,
 - ii. $z \in (Label(w_i))^{\mathcal{I}}$,
 - iii. $\langle y, z \rangle \in R^{\mathcal{I}}$ for all $R \in CELabelR(w_i)$,
 - iv. w_i is “maximal” in the sense that there does not exist any successor $w'_i \neq w_i$ of v such that

- $Label(w'_i) \supseteq Label(w_i)$ and $CELabelR(w'_i) \supseteq CELabelR(w_i)$,
- $CELabelT(w'_i) = \text{checkingFeasibility}$,
- $z \in (Label(w'_i))^{\mathcal{I}}$,
- $\langle y, z \rangle \in R^{\mathcal{I}}$ for all $R \in CELabelR(w'_i)$;
- (b) for each $1 \leq i \leq k$, set $n_{w_i} := n_{w_i} + 1$.
- 3. $\mathcal{S}_0 := \{x_w = n_w \mid w \text{ is a successor of } v\}$.
- 4. Let $w_1, \dots, w_k$ be all the successors of v defined as in the step 2a for the case $z = x$.
- 5. For each $1 \leq i \leq k$ do:
 - (a) if there exists $\succeq n S.D \in Label(v)$ such that $S \in CELabelR(w_i)$, $D \in Label(w_i)$, $S^- \notin CELabelR(u_1)$ and $\overline{D} \notin \text{FullLabel}(u_0)$ then
 - i. set $n_{w_i} := n_{w_i} + 1$.
- 6. $\mathcal{S} := \{x_w = n_w \mid w \text{ is a successor of } v\}$.

We prove that $\mathcal{S}$ is a solution for $ILConstraints(v)$.

We first show that, for any w_i at the step 2a or 4, $\langle y, z \rangle \notin S^{\mathcal{I}}$ for all $(\neg S) \in \text{CEFullLabelR}(w_i)$. Let $(\neg S) \in \text{CEFullLabelR}(w_i)$. Thus, there exist R, w', m, C, n, D such that: $S \sqsubseteq_{\mathcal{R}} R$, $R \in CELabelR(w_i)$, w' is a node in the local graph of w_i , $Label(w')$ contains $\leq m R^- . C$ as well as $\exists S^- . D$ or $\geq n S^- . D$ with $n > 0$, $C \in \text{FullLabel}(v)$ and $\overline{D} \notin \text{FullLabel}(v)$. As $Status(v) \neq \text{incomplete}$ and the rule (KCC₅) was not applicable to w' , either $\exists S . \top_R$ or $\forall S . \perp$ must belong to $Label(v)$. If $\forall S . \perp \in Label(v)$ then, since $y \in (Label(v))^{\mathcal{I}}$, we have that $y \in (\forall S . \perp)^{\mathcal{I}}$ and therefore $\langle y, z \rangle \notin S^{\mathcal{I}}$. Suppose $\exists S . \top_R \in Label(v)$. If $\langle y, z \rangle \in S^{\mathcal{I}}$ then, by the nature of the transitional full-expansion rule and the maximality of w_i , we have that $\top_R \in Label(w_i)$ and $S \in CELabelR(w_i)$, which contradicts the assumption $(\neg S) \in \text{CEFullLabelR}(w_i)$. Therefore, $\langle y, z \rangle \notin S^{\mathcal{I}}$.

We now show that if a constraint $x_w = 0$ was added into $ILConstraints(v)$ because w got status closed then n_w was not increased and hence must be 0. For the contrary, suppose the constraint $x_w = 0$ was added into $ILConstraints(v)$ (because w got status closed) and n_w was increased at least once. Thus, there exists $z \in Z \cup \{x\}$ such that $z \in (Label(w))^{\mathcal{I}}$ and $\langle y, z \rangle \in R^{\mathcal{I}}$ for all $R \in CELabelR(w)$. By the assertion stated in the above paragraph, we also have that $\langle y, z \rangle \notin S^{\mathcal{I}}$ for all $(\neg S) \in \text{CEFullLabelR}(w)$. By (1), we have that $y \in (Label(v))^{\mathcal{I}}$ and $S\text{Type}(v) = \text{simple}$, and by Lemma 4.2, it follows that $y \in (\text{FullLabel}(v))^{\mathcal{I}}$. This situation contradicts the inductive assumption 1d (with v, v_0, u, x, y replaced by w, w, v, y, z , respectively). Therefore, every constraint $x_w = 0$ from $ILConstraints(v)$ is satisfied by the solution $\mathcal{S}$.

Consider a concept $\succeq n S.D \in Label(v)$ and the corresponding constraint $\sum \{x_w \mid S \in CELabelR(w), D \in Label(w)\} \geq n$ of $ILConstraints(v)$. There are the following cases:

- Case $\geq (n+1) S.D \in Label(v)$, $S^- \in CELabelR(u_1)$ and $D \in \text{FullLabel}(u_0)$: By (1), we have that $y \in (\geq (n+1) S.D)^{\mathcal{I}}$, $\langle y, x \rangle \in S^{\mathcal{I}}$ and $x \in D^{\mathcal{I}}$. Hence, Z contains pairwise different $z_1, \dots, z_n$ such that $\langle y, z_i \rangle \in S^{\mathcal{I}}$ and $z_i \in D^{\mathcal{I}}$ for all $1 \leq i \leq n$. Each z_i makes n_w increased by 1 for some successor w of v with $S \in CELabelR(w)$ and $D \in Label(w)$. It follows that the considered constraint is satisfied by the solution $\mathcal{S}$.
- Case $(\geq n S.D \in Label(v) \text{ or } (\exists S.D \in Label(v) \text{ and } n = 1))$ and $\overline{D} \in \text{FullLabel}(u_0)$: By (1), we have that $y \in (\geq n S.D)^{\mathcal{I}}$ and $x \notin D^{\mathcal{I}}$. Analogously to the above case, the considered constraint is satisfied by the solution $\mathcal{S}$.
- Case $(\geq n S.D \in Label(v) \text{ or } (\exists S.D \in Label(v) \text{ and } n = 1))$, $\overline{D} \notin \text{FullLabel}(u_0)$ and $S^- \in CELabelR(u_1)$: By the rule (KCC₄), $D \in \text{FullLabel}(u_0)$, which implies that $\geq (n+1) S.D \in Label(v)$. Thus, this case is reduced to the first one.
- Case $(\geq n S.D \in Label(v) \text{ or } (\exists S.D \in Label(v) \text{ and } n = 1))$, $\overline{D} \notin \text{FullLabel}(u_0)$ and $S^- \notin CELabelR(u_1)$: By (1), we have that $y \in (\geq n S.D)^{\mathcal{I}}$. If $\langle y, x \rangle \notin S^{\mathcal{I}}$ or $x \notin D^{\mathcal{I}}$ then, analogously to the first case, the considered constraint is satisfied by the solution $\mathcal{S}$. Assume that $\langle y, x \rangle \in S^{\mathcal{I}}$ and $x \in D^{\mathcal{I}}$. We have that $Z \cup \{x\}$ contains pairwise different $z_1 = x, z_2, \dots, z_n$ such that $\langle y, z_i \rangle \in S^{\mathcal{I}}$ and $z_i \in D^{\mathcal{I}}$, for $1 \leq i \leq n$. Each z_i makes n_w

increased by 1 for some successor w of v with $S \in \text{CELabelR}(w)$ and $D \in \text{Label}(w)$. It follows that the considered constraint is satisfied by the solution $\mathcal{S}$.

Consider a concept $\preceq m R.C \in \text{Label}(v)$ and the corresponding constraint $\sum\{x_w \mid R \in \text{CELabelR}(w), C \in \text{Label}(w)\} \leq m$ of $\text{ILConstraints}(v)$. There are two cases:

$$\text{- case } (\leq m R.C) \in \text{Label}(v), \quad (2)$$

$$\text{- case } (\leq (m+1) R.C) \in \text{Label}(v), R^- \in \text{CELabelR}(u_1) \text{ and } C \in \text{FullLabel}(u_0). \quad (3)$$

Consider the first case, i.e., assume that (2) holds. By (1), we have that $y \in (\leq m R.C)^{\mathcal{I}}$. Hence, $Z \cup \{x\}$ contains no more than m elements z such that $\langle y, z \rangle \in R^{\mathcal{I}}$ and $z \in C^{\mathcal{I}}$. Due to the “maximality” of w and the nature of the transitional full-expansion rule, for such a z there exists at most one successor w of v such that $R \in \text{CELabelR}(w)$, $C \in \text{Label}(w)$ and the consideration of z causes n_w to be increased by 1. (Also, such an n_w is increased only due to such a z .) Therefore, the considered constraint is satisfied by the solution $\mathcal{S}$.

Consider the second case, i.e., assume that (3) holds. By (1), we have that $y \in (\leq (m+1) R.C)^{\mathcal{I}}$, $\langle y, x \rangle \in R^{\mathcal{I}}$ and $x \in C^{\mathcal{I}}$. Hence, Z contains no more than m elements z such that $\langle y, z \rangle \in R^{\mathcal{I}}$ and $z \in C^{\mathcal{I}}$. Due to the “maximality” of w and the nature of the transitional full-expansion rule, for such a z there exists at most one successor w of v such that $R \in \text{CELabelR}(w)$, $C \in \text{Label}(w)$ and the consideration of z causes n_w to be increased by 1. (Also, such an n_w is increased only due to such a z .) Therefore, the considered constraint is satisfied by $\mathcal{S}_0$. To prove that it is also satisfied by $\mathcal{S}$, it suffices to show that if n_{w_i} was increased at the step 5(a)i (in the construction of $\mathcal{S}$) then $R \notin \text{CELabelR}(w_i)$ or $C \notin \text{Label}(w_i)$.

For the contrary, suppose that n_{w_i} was increased at the step 5(a)i and

$$R \in \text{CELabelR}(w_i) \text{ and } C \in \text{Label}(w_i). \quad (4)$$

As the condition of the step 5(a)i,

$$\begin{aligned} &\text{there exists } \succeq n S.D \in \text{Label}(v) \text{ such that } S \in \text{CELabelR}(w_i), D \in \text{Label}(w_i), \\ &S^- \notin \text{CELabelR}(u_1), \overline{D} \notin \text{FullLabel}(u_0), \text{ and hence } \langle y, x \rangle \in S^{\mathcal{I}} \text{ and } x \in D^{\mathcal{I}}. \end{aligned} \quad (5)$$

Since $S^- \notin \text{CELabelR}(u_1)$ (by (5)) and $R^- \in \text{CELabelR}(u_1)$ (by (3)), we have that $R \not\sqsubseteq_{\mathcal{R}} S$.

Consider the case $S \not\sqsubseteq_{\mathcal{R}} R$. Since both S and R belong to $\text{CELabelR}(w_i)$ (by (5) and (4)), there exist roles

$$R_0 = R, R_1, \dots, R_{h-1}, R_h = S \text{ and } S_1, \dots, S_h, \text{ all belonging to } \text{CELabelR}(w_i) \quad (6)$$

such that, for every $1 \leq j \leq h$:

$$- S_j \sqsubseteq_{\mathcal{R}} R_{j-1} \text{ and } S_j \sqsubseteq_{\mathcal{R}} R_j, \quad (7)$$

$$- \text{Label}(v) \text{ contains } \exists S_j.D'_j \text{ or } \geq n_j S_j.D'_j \text{ for some } D'_j \in \text{Label}(w_i) \text{ and } n_j > 0, \quad (8)$$

$$- \text{if } j < h \text{ then } \text{Label}(v) \text{ contains } \leq m_j R_j.C'_j \text{ for some } C'_j \in \text{Label}(w_i) \text{ and } m_j. \quad (9)$$

For each j from 1 to h , observe that:

- since $S_j \in \text{CELabelR}(w_i)$, by the step 4 and the step 2(a)iii (with $z = x$) in the construction of the solution $\mathcal{S}$, we have that

$$\langle y, x \rangle \in S_j^{\mathcal{I}} \quad (10)$$

- if $S_j^- \notin \text{CELabelR}(u_1)$ then

- $(\neg S_j^-) \in \text{CEFullLabelR}(u_1)$ because one can apply the definition of CEFullLabelR (with $u, v, w, \alpha, S, R, m, C, n, D$ replaced, respectively, by $u_0, u_1, u, \text{null}, S_j^-, R_{j-1}^-, m_{j-1}, C'_{j-1}, n_j, D'_j$) due to the following reasons:
 - * by (1), $\text{AfterTrans}(u_1) = \text{true}$ and $\text{StatePred}(u_1) = u_0$,

- * $S_j^- \notin CELabelR(u_1)$ (by the premise of the above “if” clause),
 - * $S_j^- \sqsubseteq R_{j-1}^-$ (by (7))
 - * $R_{j-1}^- \in CELabelR(u_1)$ since
 - if $j = 1$ then $R_{j-1}^- = R_0^- = R^-$ (by (6)) and $R^- \in CELabelR(u_1)$ (by (3)),
 - if $j > 1$ then $R_{j-1}^- \in CELabelR(u_1)$ by induction of (11) as shown below,
 - * by (1), u is a node in the local graph of u_1 and, since $\langle u, v \rangle \in E$ and v is a state, like $Label(v)$, $Label(u)$ contains $\leq m_{j-1} R_{j-1}.C'_{j-1}$ (by (9) and (3), using $C'_0 = C$ and $m_0 = m + 1$) as well as $\exists S_j.D'_j$ or $\geq n_j S_j.D'_j$ with $n_j > 0$ (by (8)),
 - * since $R_{j-1}^- \in CELabelR(u_1)$ (as above), $(\leq m_{j-1} R_{j-1}.C'_{j-1}) \in Label(u)$ (as above) and $Status(u_0) \neq \text{incomplete}$ (by (1)), by the rule (KCC₄), either C'_{j-1} or $\overline{C'_{j-1}}$ belongs to **FullLabel**(u_0),
 - * if $j > 1$ then, since $C'_{j-1} \in Label(w_i)$ (by (9)), by the step 4 and the step 2(a)ii (with $z = x$) in the construction of the solution $\mathcal{S}$, we have that $x \in (C'_{j-1})^{\mathcal{I}}$, hence, by (1), $\overline{C'_{j-1}} \notin \text{FullLabel}(u_0)$, and by the assertion in the above item, $C'_{j-1} \in \text{FullLabel}(u_0)$,
 - * if $j = 1$ then, since $C \in \text{FullLabel}(u_0)$ (by (3)), for $C'_0 = C$ we have that $C'_{j-1} \in \text{FullLabel}(u_0)$,
 - * since $D'_j \in Label(w_i)$ (by (8)), by the step 4 and the step 2(a)ii (with $z = x$) in the construction of the solution $\mathcal{S}$, we have that $x \in (D'_j)^{\mathcal{I}}$, hence, by (1), $\overline{D'_j} \notin \text{FullLabel}(u_0)$;
 - since $(\neg S_j^-) \in \text{CEFullLabelR}(u_1)$ (shown above), by (1), $\langle y, x \rangle \notin S_j^{\mathcal{I}}$, which contradicts (10);
- hence $S_j^- \in CELabelR(u_1)$, and by (7), it follows that

$$R_j^- \in CELabelR(u_1) \quad (11)$$

As a consequence, for $j = h$, we have that $S_h^- \in CELabelR(u_1)$. Since $S_h \sqsubseteq_{\mathcal{R}} R_h$ (by (7)) and $R_h = S$ (by (6)), it follows that $S^- \in CELabelR(u_1)$, which contradicts (5).

Now consider the case $S \sqsubseteq_{\mathcal{R}} R$. One can derive $(\neg S^-) \in \text{CEFullLabelR}(u_1)$ by applying the definition of **CEFullLabelR** (with $u, v, w, \alpha, S, R, m, n$ replaced, respectively, by $u_0, u_1, u, \text{null}, S^-, R^-, m + 1$, and some n') due to the following reasons:

- by (1), **AfterTrans**(u_1) = **true** and $StatePred(u_1) = u_0$,
- $S^- \notin CELabelR(u_1)$ (by (5)), $S^- \sqsubseteq_{\mathcal{R}} R^-$ (since $S \sqsubseteq_{\mathcal{R}} R$), $R^- \in CELabelR(u_1)$ (by (3)),
- by (1), u is a node in the local graph of u_1 and, since $\langle u, v \rangle \in E$ and v is a state, like $Label(v)$, $Label(u)$ contains $(\leq (m+1) R.C)$ (by (3)) as well as $\exists S.D$ or $\geq n' S.D$ for some $n' > 0$ (since $\geq n S.D \in Label(v)$ – by (5)),
- $C \in \text{FullLabel}(u_0)$ (by (3)) and $\overline{D} \notin \text{FullLabel}(u_0)$ (by (5)).

By (1), it follows that $\langle y, x \rangle \notin S^{\mathcal{I}}$, which contradicts (5).

We have proved the induction step for the case 1(a)i when v gets status **closed** because $ILConstraints(v)$ is infeasible. The case 1(a)ii when v gets status **closed** because $ILConstraints(v)$ is infeasible can be dealt with in a similar way, using the following modifications, with $a = CELabelI(u_1)$ (and thus $x = a^{\mathcal{I}}$):

- The assumption (1) is modified by changing “ $SType(u_0) = \text{simple}$ ” to “ $SType(u_0) = \text{complex}$ ” and changing “ $\mathcal{I}$ is a model of both $\mathcal{R}$ and $\mathcal{T}$, $x \in (\text{FullLabel}(u_0))^{\mathcal{I}}$ ” to “ $\mathcal{I}$ is a model of $\langle \mathcal{R}, \mathcal{T}, \text{FullLabel}(u_0) \rangle$ ”.
- “ $D \in \text{FullLabel}(u_0)$ ” is replaced by “ $a : D \in \text{FullLabel}(u_0)$ ”, and similarly for other cases with another concept in the place of D and/or with $\notin$ instead of $\in$.
- The phrase “either C'_{j-1} or $\overline{C'_{j-1}}$ belongs to **FullLabel**(u_0)” is replaced by “either $a : C'_{j-1}$ or $a : \overline{C'_{j-1}}$ belongs to **FullLabel**(u_0)”.

- The phrase “ u , null” is replaced by “ u , a ”.

Now consider the case 1b when v gets status **closed** because $ILConstraints(v)$ is infeasible. For this case, we prove the contrapositive. Suppose that $Type(v) = \mathbf{state}$, $SType(v) = \mathbf{complex}$ and $FullLabel(v)$ is satisfiable w.r.t. $\mathcal{R}$ and $\mathcal{T}$. We show that $ILConstraints(v)$ is feasible. Let $\mathcal{I}$ be a finitely-branching model of $\mathcal{R}$, $\mathcal{T}$ and $FullLabel(v)$. We compute a solution $\mathcal{S}$ for $ILConstraints(v)$ as follows.

1. For each successor w of v , set $n_w := 0$.
2. For each individual a occurring in $\mathcal{A}$ and each $z \in \Delta^{\mathcal{I}}$ such that $\langle a^{\mathcal{I}}, z \rangle \in R^{\mathcal{I}}$ for some $R \in \mathbf{R} \cup \mathbf{R}^-$ do:
 - (a) let $w_1, \dots, w_k$ be all the successors of v such that, for each $1 \leq i \leq k$:
 - i. $CELabelT(w_i) = \text{checkingFeasibility}$ and $CELabelI(w_i) = a$,
 - ii. $z \in (Label(w_i))^{\mathcal{I}}$,
 - iii. $\langle a^{\mathcal{I}}, z \rangle \in R^{\mathcal{I}}$ for all $R \in CELabelR(w_i)$,
 - iv. w_i is “maximal” in the sense that there does not exist any successor $w'_i \neq w_i$ of v such that
 - $Label(w'_i) \supseteq Label(w_i)$ and $CELabelR(w'_i) \supseteq CELabelR(w_i)$,
 - $CELabelT(w'_i) = \text{checkingFeasibility}$ and $CELabelI(w'_i) = a$,
 - $z \in (Label(w'_i))^{\mathcal{I}}$,
 - $\langle a^{\mathcal{I}}, z \rangle \in R^{\mathcal{I}}$ for all $R \in CELabelR(w'_i)$;
 - (b) for each $1 \leq i \leq k$ do
 - i. if $z \neq b^{\mathcal{I}}$ for all b occurring in $\mathcal{A}$ then $n_{w_i} := n_{w_i} + 1$;
 - ii. else if $z = b^{\mathcal{I}}$ for some b occurring in $\mathcal{A}$ and there exists $a : (\succeq n S.D) \in Label(v)$ such that $S \in CELabelR(w_i)$, $D \in Label(w_i)$ and $S(a, b) \notin Label(v)$ then $n_{w_i} := n_{w_i} + 1$.
3. $\mathcal{S} := \{x_w = n_w \mid w \text{ is a successor of } v\}$.

We prove that $\mathcal{S}$ is a solution for $ILConstraints(v)$.

We first show that, for any w_i at the step 2a, $\langle a^{\mathcal{I}}, z \rangle \notin S^{\mathcal{I}}$ for all $(\neg S) \in \mathbf{CEFullLabelR}(w_i)$. Let $(\neg S) \in \mathbf{CEFullLabelR}(w_i)$. Thus, there exist R, w', m, C, n, D such that: $S \sqsubseteq_{\mathcal{R}} R$, $R \in CELabelR(w_i)$, w' is a node in the local graph of w_i , $Label(w')$ contains $\leq m R^- . C$ as well as $\exists S^- . D$ or $\geq n S^- . D$ with $n > 0$, $a : C \in FullLabel(v)$ and $a : \overline{D} \notin FullLabel(v)$. As $Status(v) \neq \mathbf{incomplete}$ and the rule (KCC₅) was not applicable to w' , either $a : \exists S . \top_R$ or $a : \forall S . \perp$ must belong to $Label(v)$. If $(a : \forall S . \perp) \in Label(v)$ then $a^{\mathcal{I}} \in (\forall S . \perp)^{\mathcal{I}}$ and therefore $\langle a^{\mathcal{I}}, z \rangle \notin S^{\mathcal{I}}$. Suppose $(a : \exists S . \top_R) \in Label(v)$. If $\langle a^{\mathcal{I}}, z \rangle \in S^{\mathcal{I}}$ then, by the nature of the transitional full-expansion rule and the maximality of w_i , we have that $\top_R \in Label(w_i)$ and $S \in CELabelR(w_i)$, which contradicts the assumption $(\neg S) \in \mathbf{CEFullLabelR}(w_i)$. Therefore, $\langle a^{\mathcal{I}}, z \rangle \notin S^{\mathcal{I}}$.

We now show that if a constraint $x_w = 0$ was added into $ILConstraints(v)$ because w got status **closed** then n_w was not increased and hence must be 0. For the contrary, suppose the constraint $x_w = 0$ was added into $ILConstraints(v)$ (because w got status **closed**) and n_w was increased at least once. Thus, there exists $z \in \Delta^{\mathcal{I}}$ such that $z \in (Label(w))^{\mathcal{I}}$ and $\langle a^{\mathcal{I}}, z \rangle \in R^{\mathcal{I}}$ for all $R \in CELabelR(w)$. By the assertion stated in the above paragraph, we also have that $\langle a^{\mathcal{I}}, z \rangle \notin S^{\mathcal{I}}$ for all $(\neg S) \in \mathbf{CEFullLabelR}(w)$. This situation contradicts the inductive assumption 1e (with v, v_0, u, x, y replaced by $w, w, v, a^{\mathcal{I}}, z$, respectively). Therefore, every constraint $x_w = 0$ from $ILConstraints(v)$ is satisfied by the solution $\mathcal{S}$.

Consider a concept $(a : \succeq n S.D) \in Label(v)$ and the corresponding constraint $\sum \{x_w \mid CELabelI(w) = a, S \in CELabelR(w), D \in Label(w)\} \geq n$ of $ILConstraints(v)$. Let $m = \#\{b \mid \{S(a, b), b : D\} \subseteq FullLabel(v)\}$. We have that $(a : \geq (n + m) S.D) \in Label(v)$. Since $\mathcal{I}$ is a model of $FullLabel(v)$, there exist pairwise different $z_1, \dots, z_{n+m}$ such that $\langle a^{\mathcal{I}}, z_i \rangle \in S^{\mathcal{I}}$ and $z_i \in D^{\mathcal{I}}$ for all $1 \leq i \leq n + m$. Note that, if $S(a, b) \in Label(v)$ then, by the rule (KCC₄), either $b : D \in FullLabel(v)$ or $b : \overline{D} \in FullLabel(v)$. Since $z_i \in D^{\mathcal{I}}$ and $\mathcal{I}$ is a model of $FullLabel(v)$, if $z_i = b^{\mathcal{I}}$ then $b : \overline{D} \notin FullLabel(v)$. Therefore, for every $1 \leq i \leq n + m$, if $z_i = b^{\mathcal{I}}$ and $S(a, b) \in Label(v)$ then $b : D \in FullLabel(v)$. Let $Z = \{z_1, \dots, z_{n+m}\} \setminus \{b^{\mathcal{I}} \mid S(a, b) \in Label(v)\}$.

We have that $\sharp Z = n$. Each z from Z makes n_w increased by 1 for some successor w of v with $CELabelI(w) = a$, $S \in CELabelR(w)$ and $D \in Label(w)$. It follows that the considered constraint is satisfied by the solution $\mathcal{S}$.

Consider a concept $(a : \leq n R.C) \in Label(v)$ and the corresponding constraint $\sum \{x_w \mid CELabelI(w) = a, R \in CELabelR(w), C \in Label(w)\} \leq n$ of $ILConstraints(v)$. Let $m = \sharp\{b \mid \{R(a, b), b : C\} \subseteq FullLabel(v)\}$. We have that $(a : \leq (n + m) R.C) \in Label(v)$. Since $\mathcal{I}$ is a model of $FullLabel(v)$, it follows that $a^{\mathcal{I}} \in (\leq (n + m) R.C)^{\mathcal{I}}$. Let $Z_1 = \{b^{\mathcal{I}} \mid \{R(a, b), b : C\} \subseteq FullLabel(v)\}$. Due to the subrule 3 of (NUS), we have that $\sharp Z_1 = m$.

Note that if w is a successor of v , $CELabelI(w) = a$, $R \in CELabelR(w)$ and $C \in Label(w)$ then n_w is increased only due to some z such that $\langle a^{\mathcal{I}}, z \rangle \in R^{\mathcal{I}}$ and $z \in C^{\mathcal{I}}$. Due to the “maximality” of w and the nature of the transitional full-expansion rule, for such a z there exists at most one successor w of v such that $CELabelI(w) = a$, $R \in CELabelR(w)$, $C \in Label(w)$ and the consideration of z causes n_w to be increased by 1. Since $a^{\mathcal{I}} \in (\leq (n + m) R.C)^{\mathcal{I}}$, to prove that the considered constraint is satisfied by the solution $\mathcal{S}$, it suffices to show that if $z \in Z_1$ causes n_{w_i} to be increased by 1 at the step 2(b)ii then $R \notin CELabelR(w_i)$ or $C \notin Label(w_i)$. Suppose the contrary. We have that:

$$- \{a : \leq (n + m) R.C, R(a, b), b : C\} \subseteq FullLabel(v), \quad (12)$$

$$- w_i \text{ is a successor of } v, CELabelT(w_i) = \text{checkingFeasibility} \text{ and } CELabelI(w_i) = a, \quad (13)$$

$$- b^{\mathcal{I}} \in (Label(w_i))^{\mathcal{I}} \text{ and } \langle a^{\mathcal{I}}, b^{\mathcal{I}} \rangle \in (R')^{\mathcal{I}} \text{ for all } R' \in CELabelR(w_i), \quad (14)$$

$$- a : (\geq n S.D) \in Label(v), S \in CELabelR(w_i), D \in Label(w_i) \text{ and } S(a, b) \notin Label(v), \quad (15)$$

$$- R \in CELabelR(w_i) \text{ and } C \in Label(w_i). \quad (16)$$

Since both S and R belong to $CELabelR(w_i)$ (by (15) and (16)), there exist roles

$$R_0 = R, R_1, \dots, R_{h-1}, R_h = S \text{ and } S_1, \dots, S_h, \text{ all belonging to } CELabelR(w_i) \quad (17)$$

such that, for every $1 \leq j \leq h$:

$$- S_j \sqsubseteq_{\mathcal{R}} R_{j-1} \text{ and } S_j \sqsubseteq_{\mathcal{R}} R_j, \quad (18)$$

$$- Label(v) \text{ contains } a : \exists S_j.D'_j \text{ or } a : \geq n_j S_j.D'_j \text{ for some } D'_j \in Label(w_i) \text{ and } n_j > 0, \quad (19)$$

$$- \text{if } j < h \text{ then } Label(v) \text{ contains } a : \leq m_j R_j.C'_j \text{ for some } C'_j \in Label(w_i) \text{ and } m_j. \quad (20)$$

Note that the subrule 4 of (NUS) was not applicable to v . Having (12), (17), (18) and (19), we derive that $S_1(a, b) \in Label(v)$ or $\neg S_1(a, b) \in FullLabel(v)$. Since (17) and (14), $\langle a^{\mathcal{I}}, b^{\mathcal{I}} \rangle \in S_1^{\mathcal{I}}$. Since $\mathcal{I}$ is a model of $FullLabel(v)$, it follows that $\neg S_1(a, b) \notin FullLabel(v)$, and hence $S_1(a, b) \in Label(v)$. Since $S_1 \sqsubseteq R_1$ (by (18)), by the rule (US), we also have that $R_1(a, b) \in Label(v)$. Analogously, using also (20), for every j from 1 to h , we can derive that $S_j(a, b) \in Label(v)$ and $R_j(a, b) \in Label(v)$. Since $S = R_h$, it follows that $S(a, b) \in Label(v)$, which contradicts (15). This completes the induction step for the case 1b when v gets status closed because $ILConstraints(v)$ is infeasible.

The induction steps for the other cases are straightforward. $\square$

Corollary 4.4 (Soundness of C_{SHIQ}). *If $G = \langle V, E, \nu \rangle$ is a C_{SHIQ} -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ and $Status(v) = \text{closed}$ then $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ is unsatisfiable.* $\square$

This corollary follows from the assertion 1c of Lemma 4.3.

4.3 Completeness

We prove completeness of C_{SHIQ} via model graphs. The technique has been used for other logics (e.g., in [34, 6, 22, 3]). A *model graph* (also known as a *Hintikka structure*) is a tuple $\langle \Delta, \mathbb{I}, \mathbb{C}, \mathbb{E} \rangle$, where:

- Δ is a non-empty and finite set,
- $\mathbb{I}$ is a mapping that associates each individual name with an element of Δ ,
- $\mathbb{C}$ is a mapping that associates each element of Δ with a set of concepts,
- $\mathbb{E}$ is a mapping that associates each role with a binary relation on Δ .

A model graph $\langle \Delta, \mathbb{I}, \mathbb{C}, \mathbb{E} \rangle$ is *consistent* and *$\mathcal{R}$ -saturated* if every $x \in \Delta$ satisfies:

$$- \mathbb{C}(x) \text{ does not contain } \perp \text{ nor any pair } C, \overline{C} \quad (21)$$

$$- \text{if } \langle x, y \rangle \in \mathbb{E}(R) \text{ then } \langle y, x \rangle \in \mathbb{E}(R^-) \quad (22)$$

$$- \text{if } \langle x, y \rangle \in \mathbb{E}(R) \text{ and } R \sqsubseteq_{\mathcal{R}} S \text{ then } \langle x, y \rangle \in \mathbb{E}(S) \quad (23)$$

$$- \text{if } C \sqcap D \in \mathbb{C}(x) \text{ then } \{C, D\} \subseteq \mathbb{C}(x) \quad (24)$$

$$- \text{if } C \sqcup D \in \mathbb{C}(x) \text{ then } C \in \mathbb{C}(x) \text{ or } D \in \mathbb{C}(x) \quad (25)$$

$$- \text{if } \forall S.C \in \mathbb{C}(x) \text{ and } R \sqsubseteq_{\mathcal{R}} S \text{ then } \forall R.C \in \mathbb{C}(x) \quad (26)$$

$$- \text{if } \langle x, y \rangle \in \mathbb{E}(R) \text{ and } \forall R.C \in \mathbb{C}(x) \text{ then } C \in \mathbb{C}(y) \quad (27)$$

$$- \text{if } \langle x, y \rangle \in \mathbb{E}(R), \text{trans}_{\mathcal{R}}(R) \text{ and } \forall R.C \in \mathbb{C}(x) \text{ then } \forall R.C \in \mathbb{C}(y) \quad (28)$$

$$- \text{if } \exists R.C \in \mathbb{C}(x) \text{ then } \exists y \in \Delta \text{ such that } \langle x, y \rangle \in \mathbb{E}(R) \text{ and } C \in \mathbb{C}(y) \quad (29)$$

$$- \text{if } (\geq n R.C) \in \mathbb{C}(x) \text{ then } \#\{\langle x, y \rangle \in \mathbb{E}(R) \mid C \in \mathbb{C}(y)\} \geq n \quad (30)$$

$$- \text{if } (\leq n R.C) \in \mathbb{C}(x) \text{ then } \#\{\langle x, y \rangle \in \mathbb{E}(R) \mid C \in \mathbb{C}(y)\} \leq n \quad (31)$$

$$- \text{if } (\leq n R.C) \in \mathbb{C}(x) \text{ and } \langle x, y \rangle \in \mathbb{E}(R) \text{ then } C \in \mathbb{C}(y) \text{ or } \overline{C} \in \mathbb{C}(y). \quad (32)$$

Given a model graph $M = \langle \Delta, \mathbb{I}, \mathbb{C}, \mathbb{E} \rangle$, the $\mathcal{R}$ -model corresponding to M is the interpretation $\mathcal{I} = \langle \Delta, \cdot^{\mathcal{I}} \rangle$ where:

- $a^{\mathcal{I}} = \mathbb{I}(a)$ for every individual name a ,
- $A^{\mathcal{I}} = \{x \in \Delta \mid A \in \mathbb{C}(x)\}$ for every concept name A ,
- $r^{\mathcal{I}} = \mathbb{E}'(r)$ for every role name $r \in \mathbf{R}$, where $\mathbb{E}'(R)$ for $R \in \mathbf{R} \cup \mathbf{R}^-$ are the smallest binary relations on Δ such that:
 - $\mathbb{E}(R) \subseteq \mathbb{E}'(R)$,
 - if $R \sqsubseteq_{\mathcal{R}} S$ then $\mathbb{E}'(R) \subseteq \mathbb{E}'(S)$,
 - if $\text{trans}_{\mathcal{R}}(R)$ then $\mathbb{E}'(R) \circ \mathbb{E}'(R) \subseteq \mathbb{E}'(R)$.

Note that the smallest binary relations mentioned above always exist: for each $R \in \mathbf{R} \cup \mathbf{R}^-$, initialize $\mathbb{E}'(R)$ with $\mathbb{E}(R)$; then, while one of the above mentioned condition is not satisfied, extend the corresponding $\mathbb{E}'(R)$ minimally to satisfy the condition.

Lemma 4.5. *If $\mathcal{I}$ is the $\mathcal{R}$ -model corresponding to a consistent $\mathcal{R}$ -saturated model graph $\langle \Delta, \mathbb{I}, \mathbb{C}, \mathbb{E} \rangle$, then $\mathcal{I}$ is a model of $\mathcal{R}$ and, for every $x \in \Delta$ and $C \in \mathbb{C}(x)$, we have that $x \in C^{\mathcal{I}}$.* $\square$

The first assertion of this lemma clearly holds. The second assertion can be proved by induction on the structure of C in a straightforward way.

Let $G = \langle V, E, \nu \rangle$ be a C_{SHIQ} -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ and $v \in V$ be a non-state with $\text{Status}(v) \neq \text{closed}$. A *saturation path* of v is a sequence $v_0 = v, v_1, \dots, v_k$ of nodes of G , with $k \geq 1$, such that $\text{Type}(v_k) = \text{state}$ and

- for every $0 \leq i < k$, $\text{Type}(v_i) = \text{non-state}$, $\text{Status}(v_i) \neq \text{closed}$ and $\langle v_i, v_{i+1} \rangle \in E$,
- $\text{Status}(v_k) \notin \{\text{closed}, \text{incomplete}\}$.

Observe that each saturation path of v is finite.⁵ Furthermore, if v_i is a non-state with $\text{Status}(v_i) \neq \text{closed}$ then v_i has a successor v_{i+1} with $\text{Status}(v_{i+1}) \neq \text{closed}$; if v_i is a non-state with only one successor v_{i+1} which is a state then $\text{Status}(v_{i+1}) \neq \text{incomplete}$, because after

⁵ If a non-state v_{i+1} is a successor of a non-state v_i then $\text{RFmls}(v_{i+1}) \supseteq \text{RFmls}(v_i)$ and either $\text{RFmls}(v_{i+1}) \supset \text{RFmls}(v_i)$ or $\text{FullLabel}(v_{i+1}) \supset \text{FullLabel}(v_i)$. Recall also that $\text{RFmls}(v_{i+1})$ and $\text{FullLabel}(v_{i+1})$ are subsets of $\text{closure}(\mathcal{R}, \mathcal{T}, \mathcal{A})$.

a state gets status *incomplete* all edges coming to its are deleted. Therefore, v has at least one saturation path.

Lemma 4.6 (Completeness of C_{SHIQ}). *Let $G = \langle V, E, \nu \rangle$ be a C_{SHIQ} -tableau for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$. Suppose $Status(\nu) \neq \text{closed}$. Then $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ is satisfiable.*

Proof. Let $v_0 = \nu, v_1, \dots, v_k$ be a saturation path of ν . We define a model graph $M = \langle \Delta, \mathbb{I}, \mathbb{C}, \mathbb{E} \rangle$ as follows:

1. Let Δ_0 be the set of all individuals occurring in $Label(v_k)$ and set $\Delta := \Delta_0$. For $a \in \Delta_0$, define $\mathbb{I}(a) = a$. Extend $\mathbb{I}$ to other individuals from $\mathbf{I}$ so that: if $(a \dot{=} b) \in R\mathcal{F}mls(v_k)$ then $\mathbb{I}(a) = \mathbb{I}(b)$; if $a \in \mathbf{I}$ does not occur in $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ then $\mathbb{I}(a)$ is some individual occurring in $Label(v_k)$. For each $a \in \Delta_0$, mark a as *unresolved*⁶ and set $\mathbb{C}(a) := \{C \mid (a:C) \in \text{FullLabel}(v_k)\}$. For each role R , set $\mathbb{E}(R) := \{\langle a, b \rangle \mid R(a, b) \in \text{FullLabel}(v_k)\}$.
2. For every unresolved node $y \in \Delta$ do:
 - (a) If $y \in \Delta_0$ then let $u = v_k$ and $W = \{w \in V \mid \langle v_k, w \rangle \in E \text{ and } CELabelI(w) = y\}$.
 - (b) Else let $u = f(y)$ (f is a constructed mapping that associates each node of M not belonging to Δ_0 with a simple state of G ; as a maintained property of f , $Status(u) \notin \{\text{closed}, \text{incomplete}\}$) and let $W = \{w \in V \mid \langle u, w \rangle \in E\}$.
 - (c) Fix a solution of $ILConstraints(u)$, and for each $w \in W$:
 - if $CELabelT(w) = \text{testingClosedness}$ then let $n_w = 1$,
 - else let n_w be the value of x_w in that solution.
 - (d) Delete from W elements w with $n_w = 0$.
 - (e) For each $w_0 \in W$ do:
 - Let $w_0, \dots, w_h$ be a saturation path of w_0 in G .
 - For $i := 1$ to n_{w_0} do:
 - Add a new element z into Δ .
 - For each $R \in CELabelR(w_0)$, add $\langle y, z \rangle$ into $\mathbb{E}(R)$ and $\langle z, y \rangle$ into $\mathbb{E}(R^-)$.
 - Set $\mathbb{C}(z)$ to the set of concepts belonging to $\text{FullLabel}(w_h)$ and set $f(z) := w_h$.
 - (f) Mark y as *resolved*.

The defined model graph M may be infinite. It consists of a finite base created at the step 1 and disjoint trees (with backward edges to predecessors) created at the step 2.

It is straightforward to prove that M is a consistent $\mathcal{R}$ -saturated model graph.

By the definition of C_{SHIQ} -tableaux for $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$ and the construction of M : if $(a:C) \in \mathcal{A}$ then $C \in \mathbb{C}(\mathbb{I}(a))$; if $R(a, b) \in \mathcal{A}$ then $\langle \mathbb{I}(a), \mathbb{I}(b) \rangle \in \mathbb{E}(R)$; if $(a \neq b) \in \mathcal{A}$ then $\mathbb{I}(a) \neq \mathbb{I}(b)$; and $\mathcal{T} \subseteq \mathbb{C}(y)$ for all $y \in \Delta_0$. We also have that $\mathcal{T} \subseteq \mathbb{C}(z)$ for all $z \in \Delta - \Delta_0$. Hence, by Lemma 4.5, the interpretation corresponding to M is a model of $\langle \mathcal{R}, \mathcal{T}, \mathcal{A} \rangle$. $\square$

5 Concluding Remarks

We have developed the first EXPTIME tableau decision procedure for checking satisfiability of a knowledge base in the DL $\mathcal{SHIQ}$. The complexity is measured using binary representation for numbers. Our procedure has been designed to increase efficiency of reasoning:

- We use global state caching but not global caching plus inefficient cuts although the latter approach is much simpler and still guarantees the optimal complexity.
- We use global state caching but not “pairwise” global state caching, cf. the lift from anywhere blocking to pairwise anywhere blocking [18]. This is a good optimization technique, as such a lift would make the graph larger and significantly reduce the chance of getting cache hits. It is a new technique for dealing with both inverse roles and quantified number restrictions.

⁶ Each node of M will be marked either as unresolved or as resolved.

- Similarly to our previous works [25,26,24], but in contrast to [12,13], if v is a non-state such that **AfterTrans**(v) holds then we also apply global caching for the local graph of v .
- Using rules with the highest priority for updating statuses of nodes means that the final statuses **closed**, **open** and **incomplete** of nodes are propagated “on-the-fly”.
- In contrast to Farsiniamarj’s method of exploiting integer programming for tableaux [4], in order to avoid nondeterminism we only check feasibility and do not find and use solutions of the considered set of constraints. Thus, as far as we know, we are the first one who applied integer linear *feasibility* checking to tableaux. In the current presentation of our procedure, feasibility checking is done “on-the-fly”. However, when it turns out that such checks would better be done not “on-the-fly”, they can be delayed and executed occasionally without affecting soundness and completeness of the calculus (like checking fulfillment of eventualities in the tableau decision procedure for CPDL_{reg} in [24]).
- We do not use pre-compilation techniques. Our operations are direct and natural. (Of course, not all pre-compilation techniques are bad.) The use of NNF for formulas is also natural and can be efficiently handled [23]. Treating TBox axioms as global assumptions is just for making the presentation simple. In practice, the absorption technique like the one discussed in [30] can be used to deal with TBox axioms.

Our tableau decision procedure for *SHIQ* is a framework, which can be implemented with various optimization techniques [23]. In [23] we established a set of optimizations that co-operates very well with global caching and various search strategies for the DL *ALC*, including formulas normalization, formulas caching, literals elimination, propagation of unsat (closedness) for parent and sibling nodes, as well as cutoffs and compacting the graph.⁷ All of these optimization techniques can be adapted for *SHIQ*, and probably, new ones can be found.

Implementing an efficient tableau reasoner for *SHIQ* is time-consuming. A preliminary implementation of our tableau decision procedure for *SHIQ* will be done first by our master student in the coming academic year. By the preliminary experimental results of [23,11] (on global caching for *ALC*) and [4] (on exploiting integer programming for *SHQ*), one can hope that our framework allows to create good reasoners for *SHIQ*.

Our work provides not only techniques for increasing efficiency of reasoning and making it scalable w.r.t. quantified number restrictions. It does provide also the first method for developing EXPTIME tableau decision procedures instead of N2EXPTIME ones [18,35] for EXPTIME description logics with quantified number restrictions. The method is also applicable to graded modal logics.

Acknowledgments

This work was supported by Polish National Science Centre grant 2011/01/B/ST6/02759.

References

1. F. Baader, D. Calvanese, D.L. McGuinness, D. Nardi, and P.F. Patel-Schneider, editors. *The description logic handbook: theory, implementation, and applications*. Cambridge University Press, New York, NY, USA, 2003.
2. F. Baader and U. Sattler. An overview of tableau algorithms for description logics. *Studia Logica*, 69:5–40, 2001.
3. B. Dunin-Kępicz, L.A. Nguyen, and A. Szalas. Converse-PDL with regular inclusion axioms: A framework for MAS logics. *J. Applied Non-Classical Logics*, 21(1):61–91, 2011.
4. N. Farsiniamarj. Combining integer programming and tableau-based reasoning: a hybrid calculus for the description logic SHQ. Master’s thesis, Concordia University, 2008.

⁷ On small matters like how to implement the procedure **FindProxy** efficiently, in [23] we used hashing, which is very practically efficient. Besides, even in the case the cost of that procedure is polynomial in the size of the graph, the complexity of our tableau decision procedure is still EXPTIME.

5. B. Glimm, I. Horrocks, and B. Motik. Optimized description logic reasoning via core blocking. In J. Giesl and R. Hähnle, editors, *Proceedings of IJCAR'2010*, volume 6173 of *LNCS*, pages 457–471. Springer, 2010.
6. R. Goré. Tableau methods for modal and temporal logics. In D'Agostino et al, editor, *Handbook of Tableau Methods*, pages 297–396. Kluwer, 1999.
7. R. Goré and L.A. Nguyen. A tableau system with automaton-labelled formulae for regular grammar logics. In B. Beckert, editor, *Proceedings of TABLEAUX 2005*, volume 3702 of *LNAI*, pages 138–152. Springer, 2005.
8. R. Goré and L.A. Nguyen. ExpTime tableaux with global caching for description logics with transitive roles, inverse roles and role hierarchies. In N. Olivetti, editor, *Proceedings of TABLEAUX 2007*, volume 4548 of *LNAI*, pages 133–148. Springer, 2007.
9. R. Goré and L.A. Nguyen. Analytic cut-free tableaux for regular modal logics of agent beliefs. In F. Sadri and K. Satoh, editors, *Proceedings of CLIMA VIII*, volume 5056 of *LNAI*, pages 268–287. Springer, 2008.
10. R. Goré and L.A. Nguyen. ExpTime tableaux for ALC using sound global caching. *Journal of Automated Reasoning*, DOI: 10.1007/s10817-011-9243-0, 2011.
11. R. Goré and L. Postniece. An experimental evaluation of global caching for ALC (system description). In P. Baumgartner, editor, *Proc. IJCAR'2008*, volume 5195 of *LNCS*, pages 299–305. Springer, 2008.
12. R. Goré and F. Widmann. Sound global state caching for $\mathcal{ALC}$ with inverse roles. In M. Giese and A. Waaler, editors, *Proceedings of TABLEAUX 2009*, volume 5607 of *LNCS*, pages 205–219. Springer, 2009.
13. R. Goré and F. Widmann. Optimal and cut-free tableaux for propositional dynamic logic with converse. In J. Giesl and R. Hähnle, editors, *Proceedings of IJCAR 2010*, volume 6173 of *LNCS*, pages 225–239. Springer, 2010.
14. V. Haarslev and R. Möller. Optimizing reasoning in description logics with qualified number restrictions. In *Proceedings of DL'2001*, pages 142–151, 2001.
15. V. Haarslev, M. Timmann, and R. Möller. Combining tableaux and algebraic methods for reasoning with qualified number restrictions. In *Proceedings of M4M-2*, 2001.
16. I. Horrocks, O. Kutz, and U. Sattler. The even more irresistible *SROIQ*. In P. Doherty, J. Mylopoulos, and C.A. Welty, editors, *Proc. of KR'2006*, pages 57–67. AAAI Press, 2006.
17. I. Horrocks and U. Sattler. A tableau decision procedure for *SHOIQ*. *J. Autom. Reasoning*, 39(3):249–276, 2007.
18. I. Horrocks, U. Sattler, and S. Tobies. Reasoning with individuals for the description logic SHIQ. In D.A. McAllester, editor, *Proceedings of CADE-17, LNCS 1831*, pages 482–496. Springer, 2000.
19. A. H. Land and A. G. Doig. An automatic method of solving discrete programming problems. *Econometrica*, 28(3):497–520, 1960.
20. R.B. Mishra and S. Kumar. Semantic web reasoners and languages. *Artif. Intell. Rev.*, 35(4):339–368, 2011.
21. B. Motik and U. Sattler. A comparison of reasoning techniques for querying large description logic aboxes. In M. Hermann and A. Voronkov, editors, *Proceedings of LPAR'2006*, volume 4246 of *LNCS*. Springer, 2006.
22. L.A. Nguyen. Analytic tableau systems and interpolation for the modal logics KB, KDB, K5, KD5. *Studia Logica*, 69(1):41–57, 2001.
23. L.A. Nguyen. An efficient tableau prover using global caching for the description logic $\mathcal{ALC}$. *Fundamenta Informaticae*, 93(1-3):273–288, 2009.
24. L.A. Nguyen. A cut-free exptime tableau decision procedure for the logic extending Converse-PDL with regular inclusion axioms. arXiv:1104.0405, 2011.
25. L.A. Nguyen. Cut-free ExpTime tableaux for checking satisfiability of a knowledge base in the description logic $\mathcal{ALCT}$. In *Proceedings of ISMIS'2011*, volume 6804 of *LNAI*, pages 465–475. Springer, 2011.
26. L.A. Nguyen. A cut-free ExpTime tableau decision procedure for the description logic SHI. In *Proceedings of ICCCI'2011 (1)*, volume 6922 of *LNCS*, pages 572–581. Springer, 2011 (see also the long version <http://arxiv.org/abs/1106.2305v1>).
27. L.A. Nguyen and A. Szalas. ExpTime tableaux for checking satisfiability of a knowledge base in the description logic ALC. In N.T. Nguyen, R. Kowalczyk, and S.-M. Chen, editors, *Proceedings of ICCCI'2009*, volume 5796 of *LNAI*, pages 437–448. Springer, 2009.
28. L.A. Nguyen and A. Szalas. An optimal tableau decision procedure for Converse-PDL. In N.-T. Nguyen, T.-D. Bui, E. Szczerbicki, and N.-B. Nguyen, editors, *Proceedings of KSE'2009*, pages 207–214. IEEE Computer Society, 2009.
29. L.A. Nguyen and A. Szalas. Checking consistency of an ABox w.r.t. global assumptions in PDL. *Fundamenta Informaticae*, 102(1):97–113, 2010.
30. L.A. Nguyen and A. Szalas. Tableaux with global caching for checking satisfiability of a knowledge base in the description logic *SH*. *T. Computational Collective Intelligence*, 1:21–38, 2010.
31. L.A. Nguyen and A. Szalas. ExpTime tableau decision procedures for regular grammar logics with converse. *Studia Logica*, 98(3):387–428, 2011.
32. H.J. Ohlbach and J. Koehler. Modal logics, description logics and arithmetic reasoning. *Artif. Intell.*, 109(1-2):1–31, 1999.
33. V.R. Pratt. A near-optimal method for reasoning about action. *J. Comp. Syst. Sci.*, 20(2):231–254, 1980.
34. W. Rautenberg. Modal tableau calculi and interpolation. *JPL*, 12:403–423, 1983.
35. S. Tobies. *Complexity results and practical algorithms for logics in knowledge representation*. PhD thesis, RWTH-Aachen, 2001.